

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index




## Electrical Labels in Dispenser

### Material Chart



| Material  | Print Method | Temperature Range                 | Features                                                                                                                                                                                    |
|-----------|--------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Polyester | Pre-Printed  | -40°F to 250°F<br>(-40° to 121°C) | Indoor/outdoor rated; laminated label material protects legend from abrasion and chemicals; resistant to UV light chemical atmosphere and abrasion; excellent life and adhesion properties. |

| Part Number | Symbol                                                                              | Description                            | Width |       | Height |       | Labels Per Pkg. | Std. Pkg. Dispenser(s) | Std. Ctn. Dispenser(s) |
|-------------|-------------------------------------------------------------------------------------|----------------------------------------|-------|-------|--------|-------|-----------------|------------------------|------------------------|
|             |                                                                                     |                                        | In.   | mm    | In.    | mm    |                 |                        |                        |
| Dispensers  |                                                                                     |                                        |       |       |        |       |                 |                        |                        |
| PLD-12^     |    | CIRCUIT NO., LOCATION                  | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-30^     |    | CAUTION                                | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-36      |    | CAUTION 120 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-37      |                                                                                     | CAUTION 220 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-38      |                                                                                     | CAUTION 240 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-43^     |    | DANGER HIGH VOLTAGE                    | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-45      |    | CAUTION 230 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-46      |                                                                                     | CAUTION 277 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-47      |                                                                                     | CAUTION 277/480 V                      | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-52      |   | ATTENTION SYMBOL (ISO 3864)            | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-56      |  | HIGH VOLTAGE SYMBOL (ISO 3864)         | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-57      |  | GROUND SYMBOL (ISO 3864)               | .75   | 19.10 | .75    | 19.10 | 300             | 1                      | 10                     |
| PLD-58      |  | STATIC AWARENESS WARNING               | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-60      |  | STATIC AWARENESS WARNING               | 3.00  | 76.20 | 1.00   | 25.40 | 100             | 1                      | 10                     |
| PLD-67      |  | DANGER HIGH VOLTAGE                    | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-68^     |  | LOCKOUT BY _____<br>DATE _____         | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-71      |  | WARNING - FOR CONTINUED PROTECTION ... | 2.00  | 50.80 | 1.00   | 25.40 | 150             | 1                      | 10                     |
| PLD-72      |  | CAUTION LOCK OUT FOR SAFETY BEFORE ... | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-74      |  | CAUTION HAZARD OF ELECTRIC SHOCK ...   | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-80      |  | INTRINSICALLY SAFE WIRING              | 1.00  | 25.40 | 1.50   | 38.10 | 200             | 1                      | 10                     |
| PLD-81      |  | SERVICE DISCONNECT                     | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |
| PLD-91      |  | CAUTION 480 V                          | 1.50  | 38.10 | 1.00   | 25.40 | 200             | 1                      | 10                     |

Order number of dispensers required in multiples of Std. Pkg.

^Can be clearly identified with Panduit permanent marking pens.