



Product: <u>8866</u> ☑

Lead Wire, #18 Str TC, Conductive PO/PO Ins, PVC Jkt, 40kV

Product Description

Low Temp Plastic Lead Wire, 18AWG (16x30) Tinned Copper, Conductive PO/PO Insulation, PVC Outer Jacket, 40kV

Technical Specifications

Product Overview

Suitable Applications: internal wiring of electronic equipments, high voltage applications

Physical Characteristics (Overall)

Conductor

4	AWG	Stranding	Material	No. of Conductors
-	18	16x30	TC - Tinned Copper	1
Conductor Count:		1		

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.057 in
Table Notes:	

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.208 in	0.015 in

Electrical Characteristics

Voltage

Breakdown Voltage	Description	Voltage Rating [V]	
80,000 DC	DC	40,000 V	
	AC (60 Hertz)	11,000 V	

Temperature Range

Non-UL Temp Rating:	80°C

Mechanical Characteristics

Bulk Cable Weight:	20 lbs/1000ft
Min Bend Radius/Minor Axis:	4.5 in

Standards

UL AWM Style Compliance:	N/A
Military Compliance:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating: N/A	
------------------------	--

Plenum/Non-Plenum

Plenum (Y/N):	No	

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
8866 002100	Red	Reel	100 ft	612825217091
8866 002500	Red	Reel	500 ft	612825217107
8866 002U500	Red	Reel	500 ft	612825217084

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision:	Revision Number: 0.277 Revision Date: 06-15-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.