




PART NUMBER	SHROUD MATERIAL
127-3701-602	STAINLESS STEEL PASSIVATED



8:1

DRAWING NO.									
C - 127-3701-601/610									
0	REVISIONS								
ENGINEERING RELEASE									
1	1-10-07	P A T	J R K	P D W	M J U	2-17-07 ECN 50900			
VERSION UPDATE									
***** * REVISION NUMBER FOLLOWED BY AN ALPHA * * CHARACTER INDICATES DRAWING CLARIFI- * * CATION OR PART NUMBER ADDITION ONLY. * *****									
1a	11-12-07	P A T	J R K	R B	M J U	J C N	11-13-07 ECN 51293		

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED
PER ASME Y 14.5M - 1994

"μSTATION"

COMPANY CONFIDENTIAL

NOTES:

1. SPECIFICATIONS:


INTERFACE DIMENSIONS: IN ACCORDANCE WITH MIL-STD-348A, SERIES SMP, CATCHER'S MTT
CONTACT RESISTANCE: INITIAL 2.0 MILLIOHM MAX, AFTER ENVIRONMENTAL NOT APPLICABLE

MECHANICAL:

ENGAGEMENT FORCE: 2 POUNDS MAX
DISENGAGEMENT FORCE: 0.5 POUNDS MIN
DURABILITY: 1000 CYCLES MIN

ENVIRONMENTAL:

(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF DSCC DWG NO. 94007)
OPERATING TEMPERATURE: -65°C TO 165°C
THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B, EXCEPT 165°C HIGH TEMP
CORROSION: MIL-STD-202, METHOD 101, CONDITION B
VIBRATION, HIGH FREQUENCY: MIL-STD-202, METHOD 204, CONDITION D
VIBRATION, RANDOM: MIL-STD-202, METHOD 214, CONDITION F

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY PAT		DATE 11-30-06		 cinch CONNECTIVITY SOLUTIONS a bel group	Cinch Connectivity Solutions P.O. Box 1732 Waseca, MN 56093 1-800-247-8256		
DECIMALS	mm	CHECKED BY PDW		DATE 2-16-07			TITLE SMP CATCHER'S MITT FLANGE MOUNT SHROUD		
.XX	_____	APPROVED BY JRK		DATE 2-16-07					
.XXX	REF								
MATL _____		RELEASE DATE		2-17-07		SHEET 2 OF 2		DRAWING NO. C - 127-3701-601/610	
FINISH _____		U/M		INCH					