

---

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

---

Part Number: 560F  
Page 1 of 2 Pages

Issue: 4  
Issue Date: 4/4/2006  
Effective Date: 5/30/2006


---

**A. Cordage Construction**

- 1) Conductor
  - a) Material Bare Copper Per ASTM B-3
  - b) AWG, Stranding 18, 41/34; Finer stranding may be used.
  
- 2) Insulation
  - a) Material Polyvinylchloride
  - b) Colors Blue, Brown & Green/Yellow
  - c) Nominal Diameter 0.077"
  
- 3) Assembly
  - a) Number of Conductors 3
  - b) Color Code Blue, Brown & Green/Yellow within Munsell® Component extended limits of deviation.  
*[Note: The stripe of the Green/Yellow insulation shall be 50% +/- 20%.]*
  - c) Fillers Optional
  - d) Shield Aluminum/Polyester, Foil Facing In, 25% Minimum Overlap.
  - e) Drain Wire 22 (7/30) AWG Tinned Copper; Finer stranding may be used.
  
- 4) Jacket
  - a) Material Polyvinylchloride
  - b) Surface Finish Smooth, non-striated
  - c) Nominal Diameter 0.260"
  - d) Color Black; within Munsell® Component limits of deviation
  - e) UL, CSA Type SVT
  - f) Jacket Marking Per UL Standard 62 and CSA C22.2 No. 49.

**B. Cord Configuration**

- 1) End 1 Molded Vinyl Connector, IEC 320-C13
- 2) End 2 Molded Vinyl Shrouded Plug, IEC 320-C14
- 3) Mold Color Black
- 4) Overall Length 39" +/- 2"



Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

---

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

---

Part Number: 560F  
Page 2 of 2 Pages

Issue: 4  
Issue Date: 4/4/2006  
Effective Date: 5/30/2006

---

**C. Industry Approvals and Ratings**

- |                                   |   |
|-----------------------------------|---|
| 1) UL                             | UL Standards 62 & 817   |
| 2) CSA                            | CSA Standards C22.2 No. 21 and No. 49   |
| 3) Cord Set Rating                | 1250 Watts 10A-125V   |
| 4) Temperature Rating             | 60°C, Minimum   |
| 5) EU Directive 2002/95/EC(RoHS): | All materials used in the manufacture and packaging of this part meet the requirement of EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. |
| 6) California Proposition 65:     | The outer surface materials of this product are in accordance with CA Proposition 65 and contain no greater than 300 ppm of lead and meet all other chemical constraints as outlined in CA Proposition 65.                |

**D. Packaging**

- |                     |                             |
|---------------------|-----------------------------|
| 1) Standard Package | 25 Pieces, Coiled in Carton |
|---------------------|-----------------------------|

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.