

5

4

3

2

1

Edge mark on first conductor

17,78

1,27 ± 0,08

AWG 28/7


Grey

0,89 ± 0,08

Cross section at flat

0,64 ± 0,18

13 x 1,27 = 16,51 ± 0,18




Wire ————— Tinned copper
 Gauge ————— AWG 28/7 0,089 mm²
 Voltage rating ————— 300 Vr.m.s
 Current rating ————— 1,3 A at 10°C rise above ambient

Capacity unbalanced ————— 78,7 pF/m nominal at 1MHz
 Impedance unbalanced ————— 75 Ω nominal
 Conductor resistance ————— 225 mΩ/m
 Propagation delay ————— 5,25 ns/m nominal
 Insulation material ————— PVC
 Temperature rating ————— -20°C (operating) to +105°C
 ————— -30°C (static)
 Insulation resistance ————— 10 000 MΩ/km

Approvals ————— UL Listed PLCC2-CL2
 ————— CSA Certified AWM FT-1

Slit section

∅ 6,60



③

②


①

- ① : Flat cable, AWG 28/7
- ② : Clear polyester
- ③ : Outer jacket: black PVC

A

09 18 014 7011	100 m (328 feet)
09 18 014 7008	30,48 m (100 feet)
Part number	Length per reel

	Mod.	Dot.	Name
EC01911	25/05/10	SC	
34612	20/09/07	PK	
33247	25/10/05	JMDR	
			HARTING EURL F-95972 Paris



All Dim. in mm
Orig. Size DIN A 4

SEK 18 round flat cable,
not shielded, 14 poles

Maßstab/
Scale



TB 09 18 014 70XX

Blatt/ Page
2 / 2