



Main

| | |
|------------------------------|------------|
| Range of product | 9050JCK |
| Product or component type | Timer |
| Time delay type | Off-delay |
| Time delay range | 0.3...30 s |
| [Uc] control circuit voltage | 48 V AC/DC |

Complementary

| | |
|---------------------------------|----------------------|
| Hold-in power consumption in VA | 2 VA |
| Line Rated Current | 10 A |
| Switch function | DPDT |
| Contacts type and composition | 2 NO + 2 NC |
| Contacts material | Silver nickel |
| Maximum switching voltage | 240 V AC |
| Mounting support | Socket |
| Pin number | 11 |
| Shape of pin | Tubular |
| Product compatibility | 8501NR61 8501NR62 |

Environment

| | |
|---------------------------------------|--|
| product certifications | CE RoHS UL listed UL recognized |
| ambient air temperature for operation | -18...150 °F |
| height | 2.4 in (61 mm) |
| width | 1.69 in (43 mm) |
| depth | 4.09 in (104 mm) |

Offer Sustainability

| | |
|--|--|
| Green Premium product | Green Premium product |
| Compliant - since 0627 - Schneider Electric declaration of conformity | Compliant - since 0627 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Nickel compounds, which is known to the State of California to cause cancer, and | Nickel compounds, which is known to the State of California to cause cancer, and |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty period

18 months