

## N-channel 600 V, 0.03 $\Omega$ typ., 68 A MDmesh™ M2 Power MOSFET in a TO-247 package

Datasheet – production data





Figure 1. Internal schematic diagram



### Features

| Order codes | $V_{DS} @ T_{Jmax}$ | $R_{DS(on)} max$ | $I_D$ |
|-------------|---------------------|------------------|-------|
| STW70N60M2  | 650 V               | 0.040 $\Omega$   | 68 A  |

- Extremely low gate charge
- Excellent output capacitance ( $C_{oss}$ ) profile
- 100% avalanche tested
- Zener-protected

### Applications

- Switching applications

### Description

This device is an N-channel Power MOSFET developed using MDmesh™ M2 technology. Thanks to its strip layout and an improved vertical structure, the device exhibits low on-resistance and optimized switching characteristics, rendering it suitable for the most demanding high efficiency converters.

Table 1. Device summary

| Order codes | Marking | Package | Packaging |
|-------------|---------|---------|-----------|
| STW70N60M2  | 70N60M2 | TO-247  | Tube      |

Contents

1      **Electrical ratings** ..... 3

2      **Electrical characteristics** ..... 4

      2.1    Electrical characteristics (curves) ..... 6

3      **Test circuits** ..... 8

4      **Package mechanical data** ..... 9

5      **Revision history** ..... 12



# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol         | Parameter                                                         | Value       | Unit               |
|----------------|-------------------------------------------------------------------|-------------|--------------------|
| $V_{GS}$       | Gate-source voltage                                               | $\pm 25$    | V                  |
| $I_D$          | Drain current (continuous) at $T_C = 25\text{ }^{\circ}\text{C}$  | 68          | A                  |
| $I_D$          | Drain current (continuous) at $T_C = 100\text{ }^{\circ}\text{C}$ | 43          | A                  |
| $I_{DM}^{(1)}$ | Drain current (pulsed)                                            | 272         | A                  |
| $P_{TOT}$      | Total dissipation at $T_C = 25\text{ }^{\circ}\text{C}$           | 450         | W                  |
| $dv/dt^{(2)}$  | Peak diode recovery voltage slope                                 | 15          | V/ns               |
| $dv/dt^{(3)}$  | MOSFET $dv/dt$ ruggedness                                         | 50          | V/ns               |
| $T_{stg}$      | Storage temperature                                               | - 55 to 150 | $^{\circ}\text{C}$ |
| $T_j$          | Max. operating junction temperature                               |             |                    |

1. Pulse width limited by safe operating area.
2.  $I_{SD} \leq 68\text{ A}$ ,  $di/dt \leq 400\text{ A}/\mu\text{s}$ ;  $V_{DS\text{ peak}} < V_{(BR)DSS}$ ,  $V_{DD} = 400\text{ V}$ .
3.  $V_{DS} \leq 480\text{ V}$

**Table 3. Thermal data**

| Symbol         | Parameter                               | Value | Unit                        |
|----------------|-----------------------------------------|-------|-----------------------------|
| $R_{thj-case}$ | Thermal resistance junction-case max    | 0.28  | $^{\circ}\text{C}/\text{W}$ |
| $R_{thj-amb}$  | Thermal resistance junction-ambient max | 50    | $^{\circ}\text{C}/\text{W}$ |

**Table 4. Avalanche characteristics**

| Symbol   | Parameter                                                                                                  | Value | Unit |
|----------|------------------------------------------------------------------------------------------------------------|-------|------|
| $I_{AR}$ | Avalanche current, repetitive or not repetitive (pulse width limited by $T_{jmax}$ )                       | 10    | A    |
| $E_{AS}$ | Single pulse avalanche energy (starting $T_j = 25^{\circ}\text{C}$ , $I_D = 10\text{ A}$ ; $V_{DD} = 50$ ) | 1500  | mJ   |

## 2 Electrical characteristics

( $T_C = 25\text{ °C}$  unless otherwise specified)

**Table 5. On /off states**

| Symbol        | Parameter                                        | Test conditions                                    | Min. | Typ.  | Max.     | Unit          |
|---------------|--------------------------------------------------|----------------------------------------------------|------|-------|----------|---------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage                   | $I_D = 1\text{ mA}$ , $V_{GS} = 0$                 | 600  |       |          | V             |
| $I_{DSS}$     | Zero gate voltage drain current ( $V_{GS} = 0$ ) | $V_{DS} = 600\text{ V}$                            |      |       | 1        | $\mu\text{A}$ |
|               |                                                  | $V_{DS} = 600\text{ V}$ , $T_C = 125\text{ °C}$    |      |       | 100      | $\mu\text{A}$ |
| $I_{GSS}$     | Gate-body leakage current ( $V_{DS} = 0$ )       | $V_{GS} = \pm 25\text{ V}$                         |      |       | $\pm 10$ | $\mu\text{A}$ |
| $V_{GS(th)}$  | Gate threshold voltage                           | $V_{DS} = V_{GS}$ , $I_D = 250\text{ }\mu\text{A}$ | 2    | 3     | 4        | V             |
| $R_{DS(on)}$  | Static drain-source on-resistance                | $V_{GS} = 10\text{ V}$ , $I_D = 34\text{ A}$       |      | 0.030 | 0.040    | $\Omega$      |

**Table 6. Dynamic**

| Symbol                     | Parameter                     | Test conditions                                                                                               | Min. | Typ. | Max. | Unit     |
|----------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------|------|------|------|----------|
| $C_{iss}$                  | Input capacitance             | $V_{DS} = 100\text{ V}$ , $f = 1\text{ MHz}$ ,<br>$V_{GS} = 0$                                                | -    | 5200 | -    | pF       |
| $C_{oss}$                  | Output capacitance            |                                                                                                               | -    | 250  | -    | pF       |
| $C_{rss}$                  | Reverse transfer capacitance  |                                                                                                               | -    | 5    | -    | pF       |
| $C_{oss\text{ eq.}}^{(1)}$ | Equivalent output capacitance | $V_{DS} = 0\text{ to }480\text{ V}$ , $V_{GS} = 0$                                                            | -    | 395  | -    | pF       |
| $R_G$                      | Intrinsic gate resistance     | $f = 1\text{ MHz}$ , $I_D = 0$                                                                                | -    | 3.3  | -    | $\Omega$ |
| $Q_g$                      | Total gate charge             | $V_{DD} = 480\text{ V}$ , $I_D = 68\text{ A}$ ,<br>$V_{GS} = 10\text{ V}$<br>(see <a href="#">Figure 15</a> ) | -    | 118  | -    | nC       |
| $Q_{gs}$                   | Gate-source charge            |                                                                                                               | -    | 25   | -    | nC       |
| $Q_{gd}$                   | Gate-drain charge             |                                                                                                               | -    | 47   | -    | nC       |

1.  $C_{oss\text{ eq.}}$  is defined as a constant equivalent capacitance giving the same charging time as  $C_{oss}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$

**Table 7. Switching times**

| Symbol       | Parameter           | Test conditions                                                                                                                                                            | Min. | Typ. | Max. | Unit |
|--------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 300\text{ V}$ , $I_D = 34\text{ A}$ ,<br>$R_G = 4.7\text{ }\Omega$ , $V_{GS} = 10\text{ V}$<br>(see <a href="#">Figure 14</a> and<br><a href="#">Figure 19</a> ) | -    | 32   | -    | ns   |
| $t_r$        | Rise time           |                                                                                                                                                                            | -    | 17   | -    | ns   |
| $t_{d(off)}$ | Turn-off-delay time |                                                                                                                                                                            | -    | 155  | -    | ns   |
| $t_f$        | Fall time           |                                                                                                                                                                            | -    | 9    | -    | ns   |

Table 8. Source drain diode

| Symbol          | Parameter                     | Test conditions                                                                                                                                               | Min. | Typ. | Max. | Unit          |
|-----------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|---------------|
| $I_{SD}$        | Source-drain current          |                                                                                                                                                               | -    |      | 68   | A             |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) |                                                                                                                                                               | -    |      | 272  | A             |
| $V_{SD}^{(2)}$  | Forward on voltage            | $I_{SD} = 68\text{ A}$ , $V_{GS} = 0$                                                                                                                         | -    | 0.98 | 1.6  | V             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 68\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$<br>$V_{DD} = 60\text{ V}$ (see <a href="#">Figure 18</a> )                                        | -    | 520  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                               | -    | 12   |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                               | -    | 45   |      | A             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 68\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$<br>$V_{DD} = 60\text{ V}$ , $T_j = 150\text{ }^\circ\text{C}$<br>(see <a href="#">Figure 18</a> ) | -    | 680  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                               | -    | 18   |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                               | -    | 50   |      | A             |

1. Pulse width limited by safe operating area.
2. Pulsed: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%

2.1 Electrical characteristics (curves)

Figure 2. Safe operating area




Figure 3. Thermal impedance




Figure 4. Output characteristics




Figure 5. Transfer characteristics




Figure 6. Gate charge vs gate-source voltage




Figure 7. Static drain-source on-resistance




Figure 8. Capacitance variations




Figure 9. Output capacitance stored energy




Figure 10. Normalized gate threshold voltage vs temperature




Figure 11. Normalized on-resistance vs temperature




Figure 12. Normalized  $V_{DS}$  vs temperature





Figure 13. Source-drain diode forward characteristics



### 3 Test circuits

**Figure 14. Switching times test circuit for resistive load**



**Figure 15. Gate charge test circuit**




**Figure 16. Test circuit for inductive load switching and diode recovery times**



**Figure 17. Unclamped inductive load test circuit**



**Figure 18. Unclamped inductive waveform**



**Figure 19. Switching time waveform**



## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

Figure 20. TO-247 drawing




Table 9. TO-247 mechanical data

| Dim. | mm.   |       |       |
|------|-------|-------|-------|
|      | Min.  | Typ.  | Max.  |
| A    | 4.85  |       | 5.15  |
| A1   | 2.20  |       | 2.60  |
| b    | 1.0   |       | 1.40  |
| b1   | 2.0   |       | 2.40  |
| b2   | 3.0   |       | 3.40  |
| c    | 0.40  |       | 0.80  |
| D    | 19.85 |       | 20.15 |
| E    | 15.45 |       | 15.75 |
| e    | 5.30  | 5.45  | 5.60  |
| L    | 14.20 |       | 14.80 |
| L1   | 3.70  |       | 4.30  |
| L2   |       | 18.50 |       |
| ØP   | 3.55  |       | 3.65  |
| ØR   | 4.50  |       | 5.50  |
| S    | 5.30  | 5.50  | 5.70  |

## 5 Revision history

**Table 10. Document revision history**

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                                                       |
|-------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 28-Feb-2013 | 1        | First release.                                                                                                                                                                                                                                                                                                                                                                |
| 13-Mar-2013 | 2        | – Minor text changes<br>– Modified: test condition in <a href="#">Table 7</a>                                                                                                                                                                                                                                                                                                 |
| 12-Dec-2013 | 3        | – Modified: title<br>– Modified: <a href="#">Table 4</a> , $R_{DS(on)}$ typical value in <a href="#">Table 5</a> , the entire typical values in <a href="#">Table 6</a> , <a href="#">7</a> and <a href="#">8</a><br>– Updated: <a href="#">Section 3: Test circuits</a><br>– Added: <a href="#">Section 2.1: Electrical characteristics (curves)</a><br>– Minor text changes |
| 01-Sep-2014 | 4        | – Updated values in <a href="#">Table 4</a><br>– Updated description and features in cover page<br>– Minor text changes                                                                                                                                                                                                                                                       |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2014 STMicroelectronics – All rights reserved