CT3130 Banana Plug Test Lead Set

Pair, Black & Red, 4mm Straight, Banana Plug to Right-Angle...

Description

Test lead pair, Black and Red. Most common lead for handheld DMMs. Right-Angle Banana Plug for the meter and straight banana plug for the probe or clip. With PVC jacketed wire, 1.00 mm2 (17 AWG), length 100 cm (40").



Technical data subject to change. © Cal Test Electronics 2018.



Datasheet

caltestelectronics.com

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of $25^{\circ}C \pm 5^{\circ}C$.

Specifications

IEC Rating	1,000 V CAT III / 600 V CAT IV
Current, Max	20 A
Resistance, Max	25 milliohms
Jacket Material	PVC
Length	100 cm (40")
Conductor Area	1.00 mm2
Wire Gauge	17 AWG
Stranding (# x dia.)	259 x 0.07
OD, mm (in)	3.8 mm (0.150")
Temperature (degrees)	-20 to +80C
RoHS (2011/65/EU)	Compliant
-	

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

Technical data subject to change. © Cal Test Electronics 2018.



caltestelectronics.com