

MICRO SWITCHFREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929**SWITCH - BASIC**

CATALOG LISTING

5SEI**5SEI**

PAGE 1 OF 1

MDRAWING
NUMBER**5**ISSUE
6

REPLACES

RELEASE NO. SR-9672

CHECK

REVISIONS

A	C051463
G J W	15 JUL 82
B	C057041A
C J H	21 MAR 85
C	C094274
D L M	MAR 99

CHECK

22 JUL 82

CHECK

FORMTEK


FO-52848-A

DRAWN

G J W 15 JUL 82

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

**CHARACTERISTICS**

OPERATING FORCE----- 5-17 OZ

RELEASE FORCE-----4 OZ MIN

RELEASE TRAVEL-----.004 MIN

DIFFERENTIAL TRAVEL-----.004 MAX

OVERTRAVEL-----.003 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT

S P D T

250 VAC----- 5 AMP
30 VOLTS DC RATINGINDUCTIVE ----SEA LEVEL-- 3 AMP
50,000 FT-- 2.5 AMPRESISTIVE ----SEA LEVEL-- 5 AMP
50,000 FT-- 5 AMP

MAXIMUM INRUSH -----24 AMP

SCALE FULL

DO NOT SCALE PRINT

TOLERANCESAPPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE $\pm$

NO PLACES	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
ONE PLACE	X	17.04	X X	0.87/03
TWO PLACES	X,X	0.47/018	X X X	0.367/015
THREE PLACES	X,X,X	0.167/008	X X X X	0.137/005
ANGLES				

SI METRIC

US CUSTOMARY

DESIGN UNITS ☐☒WEIGHT **3**