


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF22140-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	730 @ 0°C	340	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
						MINIATURE COLD CATHODE FLUORESCENT LAMP					
A DIM LINE CORRECT. AND 140 +/- 5.0 TO 140 +/- 3.0 RELEASED		10/17/00 L. WENGSTROM		APPVD BY DATE FD 10/17/00		SIZE A FSCM NO. 55335		DRAWING NO. BF22140-24B			
REV. NO.		DESCRIPTION/ECO NUMBER		APPVD DATE		SCALE NONE		RELEASED DATE 6/7/00		REVISION DATE 10/17/00	
				- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				REV. NO. A		SHEET 1 OF 1	