ZBVG33



Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Light block
Device short name	ZBV
Sale per indivisible quantity	5
Connections - terminals	Faston connector(1 x 6.35 mm) Faston connector(2 x 2.8 mm)
Signalling type	Steady
Light source	Protected LED
Bulb base	Integral LED
Light block supply	Direct
Light source colour	Green
[Us] rated supply voltage	110120 V AC, 50/60 Hz

Complementary

Product weight	0.04 lb(US) (0.017 kg)	
Current consumption	14 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2	
Compatibility code	ZBV	

Environment

protective treatment	ТН	
ambient air temperature for storage	-40158 °F (-4070 °C)	
ambient air temperature for operation	-40158 °F (-4070 °C)	
IP degree of protection	IP20 conforming to IEC 60529	
standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14	
resistance to fast transients	2 kV conforming to IEC 61000-4-4	
resistance to electromagnetic fields	9.14 V/yd (10 V/m) conforming to IEC 61000-4-3	
esistance to electrostatic discharge 6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2		
electromagnetic emission	Class B conforming to IEC 55011	

Offer Sustainability

WARNING: This product can expose you to chemicals WARNING: This product can expose you to chemicals including:

including:	
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

		e de la companya de
('ontractua	l warranty

Warranty period 18 months		
---------------------------	--	--

