



Product: [3093A](#) 

ControlBus™, Coax RG6, #18 Sol BCCS, FEP Ins, QUAD AL Shld, PVDF Jkt, CMP High Temp 150C

 [Request Sample](#)

Product Description

ControlBus™, Coax RG6 18AWG (Solid) Bare Copper Covered Steel, FEP Insulation, Overall Duofoil®+ Aluminum Braid(60%)+Overall Duofoil®+Aluminum Braid(40%) Shield, PVDF Outer Jacket, CMP High Temp 150C

Technical Specifications

Product Overview

Suitable Applications: harsh environment, factory automation, ControlNet™, Modbus II, Industrial Coax, Belden ControlNet cables provide maximum signal integrity and run length exceeding the high-speed, time-critical requirements necessary for ControlNet factory floor applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Solid	BCCS - Bare Copper Covered Steel	0.04 in	1

Conductor Count: 1

Insulation

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	0.17 in

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Alum / Poly / Alum	Bonded Duofoil®	100%
Braid	2	Aluminum		60%
Tape	3	Alum / Poly / Alum	Duofoil®	100%
Braid	4	Aluminum		40%

Outer Jacket Material

Material	Nominal Diameter
PVDF - Polyvinylidene Fluoride	0.274 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
28 Ohm/1000ft	3.6 Ohm/1000ft	3.6 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
16.3 pF/ft

Inductance

Nominal Inductance
0.093 µH/ft

Impedance

Nominal Characteristic Impedance
100 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.36 dB/100ft
2 MHz	0.38 dB/100ft
5 MHz	0.5 dB/100ft
10 MHz	0.65 dB/100ft
20 MHz	0.95 dB/100ft
50 MHz	1.5 dB/100ft
100 MHz	2.12 dB/100ft
200 MHz	2.99 dB/100ft
300 MHz	3.66 dB/100ft
400 MHz	4.23 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.28 ns/ft	82%

High Freq

Frequency [MHz]	Min. SRL (Structural Return Loss)
1 MHz	23 dB
2 MHz	
5 MHz	
10 MHz	
20 MHz	
50 MHz	
100 MHz	
200 MHz	
300 MHz	
400 MHz	

Temperature Range

UL Temp Rating:	150°C
Operating Temp Range:	-20°C To +150°C

Mechanical Characteristics

Bulk Cable Weight:	43 lbs/1000ft
Max. Pull Tension:	104 lbs
Min Bend Radius/Minor Axis:	2.75 in

Standards

NEC Articles:	Article 800
NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP
RG Type:	6/U Type

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Burial:	Yes
-----------------------	-----

Suitability - Outdoor:	Yes
------------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Part Number

Non-Plenum Number:	3092A
--------------------	-------

Variants

Item #	Color	Putup Type	Length	UPC
3093A 0101000	Black	Reel	1,000 ft	612825141464
3093A 0102500	Black	Reel	2,500 ft	612825141488
3093A 0105000	Black	Reel	5,000 ft	612825141495

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	N - FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Product Notes

Notes:	Blue available as standard in 1000-ft put-up only. Suitable for Outdoor and Direct Burial applications.
--------	---

History

Update and Revision:	Revision Number: 0.319 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.