



## 1. SPECIFICATIONS

PARAMETER	VALUE
Number of Conductors	10
Cable Type	Flat Cable, Unshielded
Wire Gage	28 AWG
Cable Length	6.0" (Inches)
Color	Multiple (Resistor Color Code)
Connectors	Each Strand: 0.026" I.D. Pin Socket. Female Socket: 5X2 IDC, 0.10" [2.54mm] pitch, with 0.14" wide center polarizing key.
Mating Connectors	Assmann Electronics P/N: AWHW10G-0202-T-R Sullins Connector Solutions P/N: SBH11-PBPC-D05-ST-xx Tyco Electronics / AMP P/N: 5-146257-5

## **KXACC-083: Female 10-Pin Split Ribbon Cable**

---

<b>Ordering Part Number</b>	<b>Package/Case</b>	<b>Operating Temp.</b>	<b>Packaging</b>
KXACC-083	N/A	N/A	Bulk

### **Contact Information**

**Keterex, Inc.**  
**7320 N. Mo Pac Expressway**  
**Suite 201**  
**Austin, Texas 78731**  
**Tel: 512-346-8800**  
**[www.keterex.com](http://www.keterex.com)**  
**Email: [support@keterex.com](mailto:support@keterex.com)**

Information furnished by Keterex, Inc. in this document is believed to be accurate and reliable. However, no responsibility is assumed for its use. Information in this document is subject to change without notice.

**Trademarks:** The Keterex name and logo are registered trademarks of Keterex Incorporated. Other products or brand names mentioned herein are trademarks or registered trademarks of their respective holders.

---