

10	9	8	7	6	5	4	3	2	1																																																							
<table><tr><td>PART NUMBER</td><td>ENGINEERING NUMBER</td><td>FINISH LENGTH</td></tr><tr><td>1300660090</td><td>1R4006A28M005G</td><td>1.64' [0.5M]</td></tr><tr><td>1300660092</td><td>1R4006A28M010G</td><td>3.28' [1M]</td></tr><tr><td>1300660093</td><td>1R4006A28M020G</td><td>6.56' [2M]</td></tr></table>			PART NUMBER	ENGINEERING NUMBER	FINISH LENGTH	1300660090	1R4006A28M005G	1.64' [0.5M]	1300660092	1R4006A28M010G	3.28' [1M]	1300660093	1R4006A28M020G	6.56' [2M]	1R4006A28M005G FINISHED LENGTH: M005= 0.5 METER M010= 1 METER M100= 10 METER				CABLE LENGTH TOLERANCES >.3M [1FT]: +19mm-0 [+.75in-0] .3 - .9M [1 - 3FT]: +44.5mm-0 [+1.75in-0] .9 - 1.8M [3 - 6FT]: +55.6mm-0 [+2.19in-0] 1.8 - 3.7M [6 - 12FT]: +88.9mm-0 [+3.50in-0] 3.7 - 7.3M [12 - 24FT]: +165.1mm-0 [+6.50in-0] 7.3-14.6M [24 - 48FT]: +317.5mm-0 [+12.50in-0] 14.6 - 30.5M [48-100FT]: +622.3mm-0 [+24.50in-0] OVER 30M [100FT] +2% OF FINISHED LENGTH																																													
PART NUMBER	ENGINEERING NUMBER	FINISH LENGTH																																																														
1300660090	1R4006A28M005G	1.64' [0.5M]																																																														
1300660092	1R4006A28M010G	3.28' [1M]																																																														
1300660093	1R4006A28M020G	6.56' [2M]																																																														
Ø.880 22.35 REF. KNOCKOUT HOLE 1-BLK 2-WHT 3-RED 4-GRN/YEL NOTES: 1. MATERIAL: AS NOTED 2. FINISH: AS NOTED 3. ELECTRICAL: VOLTAGE: 483V PER IEC60664 600V PER UL2237 CURRENT: 15A 4. TEMP RATING: -20°TO +90°C 5. PROTECTION: IP67 (WHEN MATED) 6. COUPLING THREAD: 7/8-16UN 7. UL LISTED FILE E258922 8. ALL DIMS ARE FOR REFERENCE UNLESS NOTED OTHERWISE			1.11 27.9 .63 16.0 1/2 NPT 4.00 101.6 .19 4.8 .38 9.7 FINISHED LENGTH																																																													
<table><tr><td>6</td><td>FLAG LABEL</td><td>VINYL</td><td>BLACK/YELLOW</td></tr><tr><td>5</td><td>POTTING MATERIAL</td><td>EPOXY</td><td></td></tr><tr><td>4</td><td>WIRE, 14 AWG, UL 1015(B)</td><td>PVC INSULATION</td><td>SEE FACE VIEW</td></tr><tr><td>3</td><td>CONTACT PIN</td><td>COPPER ALLOY</td><td>GOLD PLATED</td></tr><tr><td>2</td><td>MALE INSERT</td><td>PVC</td><td>BLACK</td></tr><tr><td>1</td><td>RECEPTACLE SHELL</td><td>ZINC DIE-CAST</td><td>BLACK</td></tr><tr><td>ITEM</td><td>DESCRIPTION</td><td>MATERIAL</td><td>FINISH</td></tr></table>			6	FLAG LABEL	VINYL	BLACK/YELLOW	5	POTTING MATERIAL	EPOXY		4	WIRE, 14 AWG, UL 1015(B)	PVC INSULATION	SEE FACE VIEW	3	CONTACT PIN	COPPER ALLOY	GOLD PLATED	2	MALE INSERT	PVC	BLACK	1	RECEPTACLE SHELL	ZINC DIE-CAST	BLACK	ITEM	DESCRIPTION	MATERIAL	FINISH	<table><tr><td colspan="2">UL 1015 WAS THHN EC NO: IPG2019-0320 DRWN: JCAPPOZZ 2019/01/09 CHKD: RSTONE 2019/01/09 APPR: BWOODMAN2017/01/26</td><td rowspan="2">QUALITY SYMBOLS ▽=0 ▽C=0</td><td>GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2">DIMENSION STYLE INCH/MM</td><td>SCALE ---</td><td>DESIGN UNITS INCH</td><td colspan="2">THIRD ANGLE PROJECTION</td></tr><tr><td colspan="2">B</td><td>mm INCH</td><td colspan="2">DRAWN BY DATE RSTONE 2017/01/11 CHECKED BY DATE M ZIELIN 2017/01/26 APPROVED BY DATE BWOODMAN 2017/01/26 MATERIAL NO. SEE P/N CHART</td><td colspan="2">TITLE MINI-CHANGE RECEPTACLE MALE, 4P, 14 AWG 1/2 NPT, AC COLOR MOLEX INCORPORATED DOCUMENT NO. SD-130066-080 SHEET NO. 1 OF 1</td></tr><tr><td colspan="2"></td><td>REV</td><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="2">SIZE B</td><td colspan="3">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr></table>							UL 1015 WAS THHN EC NO: IPG2019-0320 DRWN: JCAPPOZZ 2019/01/09 CHKD: RSTONE 2019/01/09 APPR: BWOODMAN2017/01/26		QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE INCH/MM		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		B		mm INCH	DRAWN BY DATE RSTONE 2017/01/11 CHECKED BY DATE M ZIELIN 2017/01/26 APPROVED BY DATE BWOODMAN 2017/01/26 MATERIAL NO. SEE P/N CHART		TITLE MINI-CHANGE RECEPTACLE MALE, 4P, 14 AWG 1/2 NPT, AC COLOR MOLEX INCORPORATED DOCUMENT NO. SD-130066-080 SHEET NO. 1 OF 1				REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
6	FLAG LABEL	VINYL	BLACK/YELLOW																																																													
5	POTTING MATERIAL	EPOXY																																																														
4	WIRE, 14 AWG, UL 1015(B)	PVC INSULATION	SEE FACE VIEW																																																													
3	CONTACT PIN	COPPER ALLOY	GOLD PLATED																																																													
2	MALE INSERT	PVC	BLACK																																																													
1	RECEPTACLE SHELL	ZINC DIE-CAST	BLACK																																																													
ITEM	DESCRIPTION	MATERIAL	FINISH																																																													
UL 1015 WAS THHN EC NO: IPG2019-0320 DRWN: JCAPPOZZ 2019/01/09 CHKD: RSTONE 2019/01/09 APPR: BWOODMAN2017/01/26		QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE INCH/MM		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION																																																								
B			mm INCH	DRAWN BY DATE RSTONE 2017/01/11 CHECKED BY DATE M ZIELIN 2017/01/26 APPROVED BY DATE BWOODMAN 2017/01/26 MATERIAL NO. SEE P/N CHART		TITLE MINI-CHANGE RECEPTACLE MALE, 4P, 14 AWG 1/2 NPT, AC COLOR MOLEX INCORPORATED DOCUMENT NO. SD-130066-080 SHEET NO. 1 OF 1																																																										
		REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																									
10	9	8	7	6	5	4	3	2	1																																																							