



**Product:** 9330 ☑

High Perform Instr, 4 Pr #22 Str TC, PVC Ins E2, IS, PVC Jkt, PLTC-ER

# Request Sample

# **Product Description**

High Performance Instrumentation, 4 Pair 22AWG (7x30) Tinned Copper, PVC Insulation E2 Color Code, Individual Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

## **Technical Specifications**

#### **Product Overview**

Suitable Applications:	Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V
Construction Details	

## Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	4	22	7x30	TC - Tinned Copper

#### Insulation

Element	Material	Thickness [in.]	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.017	Black, Red and Numbered

# Inner Shield Material

Element	Shield Type	Material	Coverage	Drainwire Type	Notes
Pair(s)	Таре	Alum / Poly	100%	22 AWG (7x30) TC	each pair

#### Outer Jacket Material

Material Thick		ess	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.042 in		0.372 in	Yes
Cable Diameter (Nominal	):	0.37	2 in	

# **Electrical Characteristics**

## Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield	Max. Current
Pair(s)	15 Ohm/1000ft	26 pF/ft	45 pF/ft	3 Amps per Conductor at 25°C

## Voltage

UL Voltage Rating
300 V (PLTC, CMG)

## **Mechanical Characteristics**

#### Temperature

remperatur	_
UL Rating	Operating
105°C	-30°C to +105°C
Table Notes	s:

## Bend Radius

Stationary Min. Installation Min.

3.7 in	3.7 in	
Max. Pull Tension	n:	110 lbs
Bulk Cable Weigl	ht:	65 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, T-29-520, 1202
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC-ER, PLTC-ER
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## **History**

Update and Revision:	Revision Number: 0.377 Revision Date: 07-31-2020

#### © 2020 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.