

RAFIX 16 - Pushbutton, non-illuminated, flush lens, square collar

1.30.070.251/0600

Legending available on request.



General information

| | |
|----------------|-------------|
| Actuator | flat lens |
| Color of lens | opaque blue |
| Form of collar | square |

Dimensions

| | |
|-------------------|------------------|
| Collar dimensions | 24.95 x 24.95 mm |
| Collar dimensions | 24.95 x 24.95 mm |
| Overall height | 7.15 mm |
| Mounting depth | 44.7 mm |
| Mounting hole | 16.2 mm |
| Key grid | 25 x 25 mm |

Mechanical design

| | |
|---------------------|----------------------------|
| Mounting | ring nut, max. 1.2 Nm |
| Contact function | according to contact block |
| Contact arrangement | according to contact block |
| Illumination | no |

Mechanical characteristics

| | |
|------------------|-------|
| Operating travel | 3 mm |
| Robustness max. | 100 N |

Other specifications

| | |
|---|--|
| Operating life (operations) | 2,000,000 cycle |
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Operation temperature min. | -25 °C |
| Ambient temp. operating max. without lamp / LED | +70 °C |
| Ambient temp. operating max. with lamp / LED | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out

