
INNOVATOR IN ELECTRONICS


Product Search Data Sheet


LFB182G45BG2D280

In Production Recommended RoHS REACH

Appearance & Shape







Note: This datasheet may be out of date

Co., Ltd.

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Please download the latest datasheet of LFB182G45BG2D280 from the official website of Murata Manufacturing

https://www.murata.com/en-us/products/productdetail?partno=LFB182G45BG2D280

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2400MHz to 2500MHz frequency range.

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Paper Tape	4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of LFB182G45BG2D280 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFB182G45BG2D280

LFB182G45BG2D280

Specifications

Applications	W-LAN(TI CC253x CC254x CC8520)	
Nominal Center Frequency(fo)	2450.00MHz	
Bandwidth(BW)	fo±50.00MHz	
Insertion Loss in BW I)	1.75dB max. (at 25°C)	
Insertion Loss in BW II)	1.95dB max. (-40 to +85°C)	
Attenuation(Absolute Value) I)	19dB min. at 4800.00 to 5000.00MHz	
Attenuation(Absolute Value) II)	19dB min. at 7200.00 to 7500.00MHz	
Balance Impedance (Differential) (Nom.)	Conjugate match to TI CC253x, CC254x, CC8520	
Unbalance Impedance (Nom.)	50Ω	
Power Capacity	500mW	
Operating Temperature Range	-40°C to 85°C	
L x W (size)	1.60x0.80mm	
Thickness(max.)	0.65mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet

Note: This datasheet may be out of date


Please download the latest datasheet of LFB182G45BG2D280 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=LFB182G45BG2D280



LFB182G45BG2D280

Product Data



Frequency Characteristics

3 of 3

Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.