

Technical drawing of the component showing dimensions and markings:

- Silk Screen Marking (Color: Silver):** LF X / X
- Dimensions:**
 - Overall width: $\varnothing 12$
 - Distance from left edge to first step: 2.1
 - Distance between steps: 5.4
 - Distance from second step to right edge: 5
 - Step height: 2- $\varnothing 0.6$
- Markings:**
 - Date Code Marking "5 E"
 - Year 5=2005
 - Month E=May.

Specifications			Notes	Revision History							
Description	Value	Unit		Version	Description		Date	Approved			
Technology	Electro-Mechanical		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		10/21/2013		J.S		
Resonant Frequency	2,048	(Hz)									
Rated Voltage	1.5	(V)									
SPL @ 10cm	70	(dBA)									
Coil Resistance	50	(ohm)									
Mount Type	Thru Hole										
Voltage Range	1 ~ 2	(V)									
Max Rated Current	10	(mA)									
Housing Material	NORYL										
Operating Temperature	-20 ~ +60	°C									
Storage Temperature	-20 ~ +60	°C									
Weight	2	(g)									
			Electro-Mechanical Transducer	TE122001-1							
DB UNLIMITED											
				Drawn by A.B.		Date 10/21/2013	Checked by C.E.		Date 10/21/2013	Approved by J.S	Date 10/21/2013