



For stripping and assembly instructions see Drawing Number: VAIN1101

Electrical Characteristics

Nominal Impedance:	50 ohms
Frequency Range:	DC to 11 GHz
VSWR	1.3:1 maximum
Insertion Loss	0.17 dB max
Operating Voltage (rms):	1500 V maximum at sea level
Dielectric Withstand Voltage (rms):	2500 V maximum at sea level
Contact Resistance:	1.0 milliohms maximum
Insulation Resistance:	5000 megohms minimum

Mechanical Characteristics

Mating Cycles:	500 cycles minimum
Interface Dimensions:	Conform to MIL-C-39012

Environmental Characteristics

Temperature Range:	-65 °C to +165 °C
--------------------	-------------------

	PART	DESCRIPTION
1	Body	Brass, nickel plated
2	Ferrule	Brass, nickel plated
3	Contact	Brass, gold plated
4	Dielectric	Teflon

DESCRIPTION OF REVISION	APPVD	ISS	DATE
Dimensions / Material Update	MS	5	03 Jun 19
Contact Dimensions updated	MS	4	24 Apr 09
Crimp dimension was 3.3mm	PDC	3	04 Oct 02
CAD Issue	SN	2	29 Jan 02
First Issue	DW	1	15 Jun 99



CINCH CONNECTORS LTD
 SHIREOAKS ROAD, WORKSOP
 S80 3HA (01909) 474131
 11 BILTON ROAD, CHELMSFORD
 CM1 2UP (01245) 342060

SCALE: Not To Scale
 DIMENSIONS: mm
 TOLERANCES:
 ± 0.2mm unless
 otherwise stated

DRAWN BY: P D Couzens
 CHECKED BY:
 APPROVED BY:
 DATE: 04 Oct 02

TITLE:
N Crimp Plug for RG214

PART NUMBER:
VN10-2019
 PAGE: 1 of 1