

CT3984

Datasheet

Probe Lead to Sth RaP - SILIC 0.82, 120cm

Individual, CAT IV DMM probe with silicone lead and right-angle...

Description

Individual DMM probe lead with 2 mm (.080) diameter x 19 mm (0.75) probe tips. With safety caps installed, probe meets 600V CAT IV per IEC 61010-031. Remove the safety caps to access standard 2 mm tips and attach optional tip accessories that snap-lock to the probe body for secure connection.

Features:

- Highly flexible silicone jacket lead wire
- 4 mm right-angle sheath banana plug connector
- Tip: Brass, Nickel plated
- Tip fits North American power sockets

Optional tip accessory pairs that snap-lock to the probe tips:

- CT3941 Extended Tips
- CT3943 Alligator Clips
- CT3945 Spade Lugs
- CT3947 Spring Hooks



Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com

All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

Specifications

IEC Rating	1,000 V CAT III/600 V CAT IV w/Cap(CAT II w/o Cap)
Current Max	10 A
Jacket Material	Silicone
Wire Gauge, AWG	18
Stranding	195 x 0.07 mm
OD	3.7 mm (0.146")
Temperature (degrees)	-20 to +80C
RoHS (2011/65/EU)	Compliant

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com

