

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [98266-0958](#)  
**Status:** **Active**  
**Overview:** [Premo-Flex™ FFC and Etched Polyimide Jumpers](#)  
**Description:** 0.50mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D), 25 Circuits, 0.229m Cable Length, 0.22mm Cable Thickness, Tin(Sn) Plating  
**Replacement Part Number:** [82-26-5820](#)

**Documents:**  
[Drawing \(PDF\)](#)  
[Product Specification PS-98266-001 \(PDF\)](#)  
[Packaging Specification PK-98266-001 \(PDF\)](#)  
[RoHS Certificate of Compliance \(PDF\)](#)

| General                       |                                                              |
|-------------------------------|--------------------------------------------------------------|
| Product Family                | Cable                                                        |
| Series                        | <a href="#">98266</a>                                        |
| Comments                      | Contacts on the same side, Type A                            |
| Crimp Quality Equipment       | Yes                                                          |
| Overview                      | <a href="#">Premo-Flex™ FFC and Etched Polyimide Jumpers</a> |
| Product Name                  | Premo-Flex™ FFC Jumper                                       |
| Replacement Part Number       | <a href="#">82-26-5820</a>                                   |
| UPC                           | 800756952611                                                 |
| Physical                      |                                                              |
| Cable Length                  | 0.229m                                                       |
| Circuits (Loaded)             | 25                                                           |
| Packaging Type                | Bag                                                          |
| Pitch - Termination Interface | 0.50mm                                                       |
| Temperature Range - Operating | -40°C to +105°C                                              |
| Wire Size AWG                 | N/A                                                          |
| Wire/Cable Type               | Flat Flex Cable                                              |

| Electrical                    |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 0.5A   |
| Voltage - Maximum             | 60V AC |

**Material Info**

**Reference - Drawing Numbers**

|                         |              |
|-------------------------|--------------|
| Packaging Specification | PK-98266-001 |
| Product Specification   | PS-98266-001 |
| Sales Drawing           | SD-98266-001 |



image - Reference only

Series

**EU RoHS**  
**ELV and RoHS**  
**Compliant**  
**REACH SVHC**  
**Not Reviewed**  
**Low-Halogen Status**  
**Not Reviewed**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**  
[98266Series](#)

**Use With**  
<a href="http://www.molex.com/link/ffc-fpc.html">Molex FFC – FPC connector</a>.  
Be sure to match like plating