SMD AUI Isolation Module

Surface Mount 16-Pin SOIC AUI Isolation Transformers













Product Features:

- Designed for AUI Ports
- UL/EN60950 Recognized
- 100% Compliance Testing
- 1500Vrms Hi-Pot
- Patented Open Frame Construction

Part Number	OCL (µH typ)	Turns Ratio	Rise Time (ns max)	PRI Cw/w (pF max)	PRI LL (µH max)	DCR (Ω max)	Temp. Range
TG01-0506NRL	50	1:1	3.0	7	0.15	0.20	0 to 70°C
TG01-0756NRL	75	1:1	3.0	7	0.15	0.20	0 to 70°C
TG01-1006NRL	100	1:1	3.0	10	0.20	0.20	0 to 70°C
TG01-1506NRL	150	1:1	3.0	12	0.20	0.25	0 to 70°C

Notes:

- 1. Please contact the factory or representative for individual datasheets or additional information
- 2. Contact factory for "LF" lead free availability

Circuit 16 15 14 13 12 11 10 9 16 15 14 13 12 11 10 9 1 2 3 4 5 6 7 8

US Patent Numbers: 5,656,985 6,297,721 B1 6,297,720 B1 6,320,489 B1 6,344,785 B1 6,662,431 B1



HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.