

## Cable - FLK 10/EZ-DR/ 600/KONFEK - 2299262

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 6 m



The illustration shows a 20-position version

### Product Features

- Unshielded



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 309.7 g  |
| Custom tariff number                 | 85444290 |
| Country of origin                    | Germany  |

### Technical data

#### General

|                                               |                                                     |
|-----------------------------------------------|-----------------------------------------------------|
| Nominal voltage $U_N$                         | < 50 V AC                                           |
|                                               | 60 V DC                                             |
| Max. current carrying capacity per path       | 1 A                                                 |
| Max. conductor resistance                     | 0.16 $\Omega$ /m                                    |
| Length of cable                               | 6 m                                                 |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                                |
| Single wire, cross section [AWG]              | 26                                                  |
| Conductor construction: Number of litz wires: | 7                                                   |
| Single wire, material                         | Cu tin-plated                                       |
| External diameter                             | 6 mm                                                |
| Cable, preassembly                            | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                                     | no                                                  |

# Cable - FLK 10/EZ-DR/ 600/KONFEK - 2299262

## Technical data

### General

|                        |               |
|------------------------|---------------|
| Outer sheath, material | PVC           |
| External sheath, color | gray RAL 7035 |

### Environmental conditions

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C                   |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C                   |
| Flame resistance                        | IEC 60332-1                        |
|                                         | DIN VDE 0482 Part 332-1            |
| Resistance to oil                       | DIN VDE 0472 Part 803, test type B |
| Gasoline resistance                     | Against occasional splashes        |

### Connector, module side

|                       |                      |
|-----------------------|----------------------|
| Connection name       | Field level          |
| Connection method     | IDC/FLK socket strip |
| Number of connections | 1                    |
| Number of positions   | 10                   |
| Pitch                 | 2.54 mm              |

### Connector, controller side

|                       |                      |
|-----------------------|----------------------|
| Connection name       | Controller level     |
| Connection method     | IDC/FLK socket strip |
| Number of connections | 1                    |
| Number of positions   | 10                   |
| Pitch                 | 2.54 mm              |

### Supported controller

|                     |                |
|---------------------|----------------|
| Controller          | Emerson DeltaV |
| - suitable I/O card | VE4002S1T2B4   |

### Standards and Regulations

|                   |                                    |
|-------------------|------------------------------------|
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Flame resistance  | IEC 60332-1                        |
|                   | DIN VDE 0482 Part 332-1            |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |

## Cable - FLK 10/EZ-DR/ 600/KONFEK - 2299262

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27249205 |
| eCl@ss 9.0 | 27242220 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000237 |
| ETIM 3.0 | EC000237 |
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11     | 26121620 |
| UNSPSC 12.01  | 26121620 |
| UNSPSC 13.2   | 26121620 |

### Approvals

#### Approvals

---

#### Approvals

#### EAC

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

|     |
|-----|
| EAC |
|-----|