



DESCRIPTION: HIGH DENSITY - FEMALE - RIGHT ANGLE

ELECTRICAL:

CURRENT RATING: 3 AMPS
CONTACT RESISTANCE: 15 MILLIOhms Max.
INSULATION RESISTANCE: 1,000 MEGOhms Min. AT 500VDC
WITHSTANDING VOLTAGE: 1,000VAC FOR 1 MINUTE
TEMPERATURE: -55°C TO +105°C

MATERIALS:

SHELL: STEEL
INSULATOR: PBT, (UL94-0)
CONTACT: COPPER ALLOY
CONTACT FINISH: SEE PART NUMBER KEY BELOW
BOARD LOCK: BRASS - TIN PLATED
RIVET INSERT: BRASS - NICKEL PLATED



181-078-2 1 3 L YY 1

SERIES 181-078-2
POSITIONS 078
GENDER 2 = FEMALE
TERMINATION 1 = DIP SOLDER
SHELL PLATING 3 = NICKEL PLATED
RoHS COMPLIANT L = LOW TEMP. PROCESS
HARDWARE OPTIONS 53 = 4-40 INSERTS / BOARDLOCKS
56 = 4-40 SCREWLOCKS / BOARDLOCKS
PLATING OPTIONS 1 = GOLD FLASH (MATING AREA)
TIN TAILS (SOLDER AREA)

DO NOT SCALE FROM DRAWING

RoHS COMPLIANT




THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: C. SMITH		DATE: 07-01-10	
SCALE: NTS		SHEET 1 OF 2	
DWG NO. 181-078-213LYY1		REV 6	

DESCRIPTION: PCB LAYOUT - RIGHT ANGLE - FEMALE





78 POSITION

HOLE PATTERN SHOWN
ARE FOR MALE


UNITS = inch

* TYP.
SUGGESTED SIZE
MAY NOT BE SUITABLE FOR ALL APPLICATIONS



53

BOARD LOCKS
IN FRONT HOLE



56

BOARD LOCKS
IN FRONT HOLE

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF NorComp AND SHALL NOT
BE REPRODUCED, COPIED OR USED AS THE
BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
C. SMITH

DATE:
07-01-10

NorComp

SCALE:
NTS

SHEET
1 OF 2

REV
6

DWG NO.
181-078-213LYY1