

## Description


The PAM2800 is a high power white LED driver with 350mA constant rated source current. It features high efficiency and low quiescent current, making it ideal for battery powered applications.

## Features

- High Efficiency 92%
- Up to 350mA Constant Source Current
- Low Quiescent Current: Typ. 65µA
- 0.5µA Shutdown Current
- Short Circuit Protection
- Open Load LED Protection
- Thermal Protection
- Space Saving Package SOT23-5
- Pb-Free Package

## Pin Assignments

Top View  
SOT23-5



## Applications

- High Power White LED Driver

## Typical Applications Circuit





Figure 1



## Pin Description

| Pin Number | Pin Name | Function                  |
|------------|----------|---------------------------|
| 1          | VIN      | Input                     |
| 2          | GND      | Ground                    |
| 3          | EN       | Chip Enable (Active High) |
| 4          | FB       | Feedback                  |
| 5          | VOUT     | Output                    |

## Absolute Maximum Ratings (@T<sub>A</sub> = +25°C, unless otherwise specified.)

These are stress ratings only and functional operation is not implied. Exposure to absolute maximum ratings for prolonged time periods may affect device reliability. All voltages are with respect to ground.

| Parameter                  | Rating                           | Unit |
|----------------------------|----------------------------------|------|
| Input Voltage              | 6                                | V    |
| Output Current             | 350                              | mA   |
| Output Pin Voltage         | GND -0.3 to V <sub>IN</sub> +0.3 | V    |
| Lead Soldering Temperature | 300, (5sec)                      | °C   |
| Storage Temperature        | -65 to +150                      | °C   |

## Recommended Operating Conditions (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Parameter              | Rating      | Unit |
|------------------------|-------------|------|
| Maximum Supply Voltage | 5.5         | V    |
| Junction Temperature   | -40 to +125 | °C   |
| Operation Temperature  | -40 to +85  |      |

## Thermal Information



| Parameter                                | Symbol         | Package | Max | Unit |
|--|----------------|---------|-----|------|
| Thermal Resistance (Junction to Case)    | $\theta_{JC}$  | SOT23-5 | 130 | °C/W |
| Thermal Resistance (Junction to Ambient) | $\theta_{JA}$  | SOT23-5 | 250 |      |
| Internal Power Dissipation               | P <sub>D</sub> | SOT23-5 | 400 | mW   |

## Electrical Characteristics (@T<sub>A</sub> = +25°C, V<sub>IN</sub> = 3.7V, C<sub>IN</sub> = 1μF, C<sub>O</sub> = 2.2μF, unless otherwise specified.)

| Parameter                   | Symbol          | Test Conditions      | Min | Typ | Max | Units |
|-----------------------------|-----------------|----------------------|-----|-----|-----|-------|
| Input Voltage               | V <sub>IN</sub> |                      |     |     | 5.5 | V     |
| Output Current              | I <sub>O</sub>  |                      | 300 |     |     | mA    |
| Quiescent Current           | I <sub>Q</sub>  | No Load              |     | 65  | 90  | μA    |
| Efficiency                  |                 |                      | 90  | 92  |     | %     |
| Over Temperature Shutdown   | OTS             | I <sub>O</sub> = 1mA |     | 150 |     | °C    |
| Over Temperature Hysteresis | OTH             | I <sub>O</sub> = 1mA |     | 30  |     | °C    |

### Typical Performance Characteristics

(@T<sub>A</sub> = +25°C, C<sub>IN</sub> = 1μF, C<sub>O</sub> = 2.2μF, R1 = 62kΩ, R2 = 33kΩ, R<sub>S</sub> = 0.22Ω, unless otherwise specified.)



---

## Application Information

---

In the typical application (see Figure 1), the LED current will come to constant current level little by little after the device is powered. A 62K $\Omega$  resistor is recommended for R1, the value for R2 should be adjusted around 33K $\Omega$  due to LED forward voltage from lot-to-lot or brand-to-brand.

### Power Dissipation and Thermal Consideration

Thermal protection limits power dissipation in the PAM2800. When the operation junction temperature exceeds +150°C, the OTP (Over Temperature Protection) starts the thermal shutdown and turns the pass transistor off. The pass transistor resumes operation after the junction temperature drops below +120°C.

For continuous operation, the junction temperature should be maintained below +125°C. The power dissipation is defined as:

$$P_D = (V_{IN} - V_{OUT}) * I_O + V_{IN} * I_{GND}$$

The maximum power dissipation depends on the thermal resistance of IC package, PCB layout, the rate of surrounding airflow and temperature difference between junction and ambient. The maximum power dissipation can be calculated by the following formula:

$$P_{D(MAX)} = (T_{J(MAX)} - T_A) / \theta_{JA}$$

Where  $T_{J(MAX)}$  is the maximum operation junction temperature +125°C.  $T_A$  is the ambient temperature, and  $\theta_{JA}$  is the thermal resistance from the junction to the ambient.


For example, as  $\theta_{JA}$  is +250°C/W for SOT-23, based on the standard JEDEC 51-3 for a single layer thermal test board, the maximum power dissipation for SOT-23 package at  $T_A = +25^\circ\text{C}$  can be calculated by following formula:

$$P_{D(MAX)} = (125^\circ\text{C} - 25^\circ\text{C}) / 250 = 0.4\text{W}$$

To calculate the junction temperature of the PAM2800 SOT-23 package, if we use input voltage  $V_{IN} = 4\text{V}$  at an output current  $I_O = 300\text{mA}$  and the case temperature  $T_A = 40^\circ\text{C}$  measured by the thermal couple while operating, the power dissipation is defined as:


$$P_D = (4\text{V} - 2.8\text{V}) * 300\text{mA} + 4\text{V} * 70\mu\text{A} \approx 360\text{mW}$$

**Ordering Information**




| Part Number | Output Current | Marking | Package Type | Standard Package     |
|-------------|----------------|---------|--------------|----------------------|
| PAM2800AABR | 350mA          | EGAYW   | SOT23-5      | 3000 Units/Tape&Reel |

**Marking Information**



EG: Product Code of PAM2800  
I: Current Code  
Y: Year  
W: Week

**Package Outline Dimensions** (All dimensions in mm.)



| REF. | Millimeter |      |
|------|------------|------|
|      | Min        | Max  |
| A    | 1.10MAX    |      |
| A1   | 0          | 0.10 |
| A2   | 0.70       | 1    |
| c    | 0.12REF.   |      |
| D    | 2.70       | 3.10 |
| E    | 2.60       | 3.00 |
| E1   | 1.40       | 1.80 |
| L    | 0.45REF.   |      |
| L1   | 0.60REF.   |      |
| θ    | 0°         | 10°  |
| b    | 0.30       | 0.50 |
| e    | 0.95REF.   |      |
| e1   | 1.90REF.   |      |

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)