



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005030	30MAR11	HMR

COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.088
CONTACT	.023

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
 TOLERANCE ON
 FRAC. DEC. ANGLES
 ± 1/64 ±.005 ± °

DRAWN BY: KRW DATE: 9/10/79
 CHECKED BY: R.R.SMITH 9/11/79
 APPD BY: GH 9/12/79
 USE ASS'Y PROCEDURE
 NO. AP. 10-002
 408-04795
 CUSTOMER DRAWING

STE TE Connectivity

TITLE OSSM STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT

SIZE B	CODE IDENT NO. 26805	1045351	REV A1
--------	----------------------	---------	--------

SCALE 8:1 SHEET 1 OF 1

NOTES:
 1. DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE