

CARMEN-RS-C

~10° spot beam. Assembly with holder C compatible with LEDiL HEKLA.

TECHNICAL SPECIFICATIONS:

Dimensions Ø 69.5 mm

Height 41.5 mm

Fastening socket

ROHS compliant yes 10



MATERIAL SPECIFICATIONS:

ComponentTypeMaterialColourFinishCARMEN-RSSingle lensPMMAclearCARMEN-HLD-CHolderPCblack


ORDERING INFORMATION:

Component Qty in box MOQ MPQ Box weight (kg)

CP15916_CARMEN-RS-C Single lens 150 15 6.2


» Box size: 480 x 280 x 300 mm







PHOTOMETRIC DATA (MEASURED):





PHOTOMETRIC DATA (MEASURED):


bridgelux

LED Vesta TW 9mm (9W) DP

FWHM 12.0°
Efficiency 56 %
Peak intensity 7.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16142_HEKLA-SOCKET-K

Bender Wirth: 489 Typ L8






CITIZEN

LED CLL02x/CLU02x (LES10)

FWHM 13.0°
Efficiency 59 %
Peak intensity 8.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C







CITIZEN

LED CLU700/701/702

FWHM 8.0°
Efficiency 62 %
Peak intensity 20.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C






CITIZEN

LED CLU700/701/702

FWHM 9.0°
Efficiency 69 %
Peak intensity 22.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15255_HEKLA-SOCKET-C





PHOTOMETRIC DATA (MEASURED):

CITIZEN


LED CLU710/711 FWHM 12.0°

Efficiency 64 % Peak intensity 11.5 cd/lm

LEDs/each optic 1 Light colour White Required components:

F15859_HEKLA-SOCKET-I





CITIZEN


LED CLU7A2 (LES 4.2mm)

FWHM 6.0° Efficiency 65 % Peak intensity 34.7 cd/lm

Peak intensity 34.7 cd/l LEDs/each optic 1 Light colour White Required components:

F15255_HEKLA-SOCKET-C






CITIZEN

LED CLU7B2
FWHM 6.0°
Efficiency 66 %
Peak intensity 43.4 cd/lm

LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C






CREE \$

LED CMA1516
FWHM 13.0°
Efficiency 63 %
Peak intensity 9.7 cd/lm
LEDs/each optic 1

Light colour White Required components:

F15256_HEKLA-SOCKET-D






Published: 04/05/2018

PHOTOMETRIC DATA (MEASURED):

CREE 💠

LED CMT14xx
FWHM 14.0°
Efficiency 40 %
Peak intensity 5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15255_HEKLA-SOCKET-C






CREE 🕏

LED CXA/B 13xx
FWHM 8.0°
Efficiency 64 %
Peak intensity 21.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15956_HEKLA-SOCKET-J






CREE 🕏

LED CXA/B 15xx
FWHM 13.0°
Efficiency 65 %
Peak intensity 11.3 cd/lm
LEDs/each optic 1

LEDs/each optic 1 Light colour White Required components: F15256_HEKLA-SOCKET-D






CREE \$

LED CXA/B 1816 & CXA/B 1820 & CXA 1850

FWHM 17.0°
Efficiency 59 %
Peak intensity 5.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15256_HEKLA-SOCKET-D







PHOTOMETRIC DATA (MEASURED):




LED LUXEON CoB 1202HD

FWHM 9.7°
Efficiency 66 %
Peak intensity 18.5 cd/lm
LEDs/each optic 1
Light colour White

F15848_HEKLA-SOCKET-G





MUMILEDS


Required components:

LED LUXEON CoB 1204HD

FWHM 13.0°
Efficiency 63 %
Peak intensity 10 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15858_HEKLA-SOCKET-H






DESCRIPTION LUMILEDS

LED LUXEON CoB 1205HD

FWHM 15.0°
Efficiency 59 %
Peak intensity 6.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15858_HEKLA-SOCKET-H






DESCRIPTION LUMILEDS

LED LUXEON CX Plus CoB - HD S01H4

FWHM 8.0°
Efficiency 67 %
Peak intensity 27.5 cd/lm
LEDs/each optic 1
Light colour White

Required components: Bender Wirth: 634c Hekla







PHOTOMETRIC DATA (MEASURED):




LUXEON CX Plus CoB - HD S04H9

FWHM 13.0° 61 % Efficiency Peak intensity 10.3 cd/lm

LEDs/each optic 1 Light colour White Required components: Bender Wirth: 634c Hekla






ELUMINUS

LED CXM-3 **FWHM** 6.0° 66 % Efficiency Peak intensity 38.5 cd/lm

LEDs/each optic 1 White Light colour Required components:

F15255_HEKLA-SOCKET-C






ELUMINUS

LED CXM-4 **FWHM** 7.0° Efficiency 63 % Peak intensity 28.1 cd/lm

LEDs/each optic 1 Light colour White Required components: F15255_HEKLA-SOCKET-C




ELUMINUS

LED CxM-9 (13.5x13.5)

FWHM 13.0° Efficiency 59 % Peak intensity 9.3 cd/lm LEDs/each optic 1 White Light colour Required components:

F15255_HEKLA-SOCKET-C








PHOTOMETRIC DATA (MEASURED):

LED Fortimo SLM L09 CoB

FWHM 13.0° 63 % Efficiency Peak intensity 9.6 cd/lm LEDs/each optic 1 Light colour White Required components: F15858_HEKLA-SOCKET-H






SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

FWHM 13.0° 60 % Efficiency Peak intensity 9.3 cd/lm LEDs/each optic 1 White Light colour Required components:

F15255_HEKLA-SOCKET-C






SAMSUNG

LED LC020C **FWHM** 11.0° Efficiency 61 % Peak intensity 12 cd/lm LEDs/each optic 1 Light colour White Required components:

F15848_HEKLA-SOCKET-G






SAMSUNG

LED LC020C G2 **FWHM** 12.0° Efficiency 59 % Peak intensity 10 cd/lm LEDs/each optic 1 White Light colour Required components:

F15859_HEKLA-SOCKET-I







PHOTOMETRIC DATA (MEASURED):


TRIDONIC


LED SLE G7 LES09

FWHM 12.0° Efficiency 61 % Peak intensity 10.9 cd/lm

LEDs/each optic 1 Light colour White Required components:

F15255_HEKLA-SOCKET-C






TRIDONIC

LED SLE G7 LES13

FWHM 17.0° 56 % Efficiency Peak intensity 5 cd/lm LEDs/each optic 1 White Light colour Required components:

F15859_HEKLA-SOCKET-I






XICATO

LED XOB 6 mm **FWHM** 9.0° Efficiency 62 % Peak intensity 20.1 cd/lm

LEDs/each optic 1 Light colour White Required components: F15255_HEKLA-SOCKET-C






XICATO

XOB 9.8 mm FWHM 12.0° Efficiency 60 % 10.4 cd/lm Peak intensity

LEDs/each optic 1 White Light colour Required components:

F15255_HEKLA-SOCKET-C







PHOTOMETRIC DATA (MEASURED):


XICATO

LED XTM - 19mm LES

FWHM 18.0°
Efficiency 50 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:

C16058_XTM-ADAPTER-50-C





Published: 04/05/2018



PHOTOMETRIC DATA (SIMULATED):

bridgelux

LED VERO13
FWHM 15.0°
Efficiency 61 %
Peak intensity 5.3 cd/lm
LEDs/each optic 1
Light colour White


Required components: C16142_HEKLA-SOCKET-K

CITIZEN

LED CLU720/721
FWHM 15.0°
Efficiency 61 %
Peak intensity 6.6 cd/lm
LEDs/each optic 1

LEDs/each optic 1
Light colour White
Required components:

F15859_HEKLA-SOCKET-I




MATERIAL PROPERTY OF THE PROP

LED LUXEON CoB Compact

FWHM 10.0°
Efficiency 71 %
Peak intensity 18 cd/lm
LEDs/each optic 1
Light colour White
Required components:

F15848_HEKLA-SOCKET-G




LUMINUS

LED CxM-6 (12x13)

FWHM 10.0°
Efficiency 68 %
Peak intensity 18.5 cd/lm

LEDs/each optic 1
Light colour White
Required components:

F15255_HEKLA-SOCKET-C



Published: 04/05/2018



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy