

## Cable gland - G-INS-PG13,5-S68N-PNES-GY - 1411143

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide, External cable diameter 6 mm ... 12 mm, Shielding: No, Connecting thread: Pg13.5, Color: silver grey

### Product Features



### Key commercial data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	11.7 GRM
Custom tariff number	39269097
Country of origin	Turkey

### Technical data

#### Dimensions

Length	40 mm
Length without connecting thread	31 mm
Connecting thread diameter	20.4 mm
Wrench size, union nut	24 mm
Wrench size, support	24 mm
Hexagon angular dimension GRP	27.8 mm
Length of the connecting thread	9 mm
External cable diameter	6 mm ... 12 mm

#### Ambient conditions

Degree of protection	IP68 (5 bar, 30 min.)
Ambient temperature (operation)	-30 °C ... 80 °C (for a short period up to 150 °C)

#### General

## Cable gland - G-INS-PG13,5-S68N-PNES-GY - 1411143

### Technical data

#### General

Cable gland material	Polyamide
Seal material	Neoprene
Cable seal material	Neoprene
Shielded	No
Thread type on connection side	Pg13.5
Torque	5 Nm ... 6 Nm (Union nut)
Inflammability class according to UL 94	V2
Color	silver grey

### Classifications

#### eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

#### ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

### Approvals

#### Approvals

Approvals

CSA / UL Recognized

Ex Approvals


Approvals submitted

#### Approval details


---

## Cable gland - G-INS-PG13,5-S68N-PNES-GY - 1411143

### Approvals

UL Recognized 

### Drawings

Dimensional drawing

