

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

1201088129

Status:

Active

Description:

Double-Ended RJ-45 Cordset, 4 Poles, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 9.0m (29.53' ) Length, 6.70mm (.264") Diameter, Green

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Documents:                    |                                                      |
| <a href="#">Drawing (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a> |

|                               |                      |
|-------------------------------|----------------------|
| General                       |                      |
| Product Family                | Industrial Cordsets  |
| Series                        | 120108               |
| Connector End A               | RJ-45 (standard)     |
| Connector End B               | RJ-45 (standard)     |
| IP Rating                     | IP20                 |
| Material - Contact            | Copper Alloy         |
| Performance Category          | 5e                   |
| Product Name                  | Industrial Ethernet  |
| Protocol                      | EtherNet             |
| Type                          | Double Ended         |
| UPC                           | 78172539509          |
| Physical                      |                      |
| Cable Diameter                | 6.70mm (.264")       |
| Cable Length                  | 9.0m (29.53')        |
| Color - Cable Jacket          | Green                |
| Coupling Style                | N/A                  |
| Gender                        | Male-Male            |
| Keyway                        | N/A                  |
| LED Indicator                 | No                   |
| Material - Cable Jacket       | PUR                  |
| Material - Connector Body     | Thermoplastic        |
| Material - Coupling Nut       | N/A                  |
| Material - Plating Mating     | Gold                 |
| Orientation                   | Straight to Straight |
| Poles                         | 4                    |
| Temperature Range - Operating | -20°C to +60°C       |
| Wire Size AWG                 | 22                   |
| Wire/Cable Type               | Shielded PUR         |
| Electrical                    |                      |
| Current - Maximum per Contact | 1.5A                 |
| Voltage - Maximum             | 30V                  |
| Material Info                 |                      |
| Engineering Number            | E66A06011M090        |
| Reference - Drawing Numbers   |                      |
| Sales Drawing                 | SD-120108-044        |

|                                                               |              |
|---------------------------------------------------------------|--------------|
| EU ELV                                                        |              |
| Not Reviewed                                                  |              |
| EU RoHS                                                       | China RoHS   |
| Not Reviewed                                                  |              |
| REACH SVHC                                                    |              |
| Not Reviewed                                                  |              |
| Halogen-Free                                                  |              |
| Status                                                        |              |
| Not Reviewed                                                  |              |
| For more information, please visit <a href="#">Contact US</a> |              |
| China ROHS                                                    | Not Reviewed |
| ELV                                                           | Not Reviewed |
| RoHS Phthalates                                               | Not Reviewed |

Search Parts in this Series

120108 Series

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION