



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	*MSCP ±25%	*LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
7683SBP	5.0	.060	.050	0.63	100,000	C-2R
7715SBP	5.0	.115	.150	1.89	40,000	C-2R
8097SBP	12.0	.060	.150	1.89	16,000	C-2F
CB48SBP	14.0	.040	.150	1.89	16,000	C-2F
8098SBP	14.0	.065	.150	1.89	16,000	C-2F
8099SBP	18.0	.026	.150	1.89	16,000	C-2F
7839SBP	28.0	.024	.150	1.89	16,000	CC-2F

*LAMP RATED ONLY (NOT IN BASE)

NOTES:

1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS.
2. BASE MATERIAL: NYLON OR EQUIVALENT.
3. BASE COLOR: WHITE.
4. PIN MATERIAL: NICKEL WIRE, GOLD PLATED.
5. LAMPS TO BE 100% AGED FOR AN EQUIVALENT TO A MINIMUM OF TEN HOURS AT RATED VOLTAGES.
6. FINAL INSPECTION ON ALL LAMPS TO BE PER: MIL. STD. 105E TO AN AQL OF 2.5.
7. DIMENSIONS NOT PROVIDING TOLERANCES ARE REFERENCE DIMENSIONS ONLY.

<p>THIRD ANGLE PROJECTION</p>	<p>METRIC</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>					
	<p>TITLE</p> <p>T-1 SPECIAL BI-PIN BASED LAMPS</p>		<p>SIZE</p> <p>A</p>	<p>FSCM NO.</p> <p>55335</p>	<p>DRAWING NO.</p> <p>BI-PIN T-1 SPECIAL</p>			
<p>REV. NO.</p> <p>A</p>	<p>DESCRIPTION/ECO NUMBER</p> <p>ADD CB48SBP-CANCEL DRAW. CB48SBP/K & CB48SBP/S</p>	<p>APPV'D DATE</p> <p>3/15/00</p>	<p>DRAWN BY</p> <p>L. WENGSTROM</p>	<p>APPV'D BY DATE</p> <p>BW 4/17/00</p>	<p>RELEASED DATE</p> <p>3/15/00</p>	<p>REVISION DATE</p> <p>4/17/00</p>	<p>REV. NO.</p> <p>A</p>	<p>SHEET</p> <p>1 OF 1</p>
<p>RELEASED - CANCEL SM-SPCBP-T 1</p>			<p>- CAD DRAWING -</p>			<p>SCALE</p> <p>NONE</p>		
<p>MANUAL REVISIONS NOT PERMITTED</p>								