

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0760551125

Status:

Active

Overview:

Impact™ Backplane Connectors and Cable Assemblies

Description:

Impact™ 100 Ohm 5 Pair Vertical Backplane Header, Unguided, Dual Endwall, 10 Columns, 150 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free

Documents:

3D Model

Application Specification AS-76060-990 (PDF)

Drawing (PDF)

Application Specification AS-76060-9999 (PDF)

Product Specification PS-76060-999 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Backplane Connectors

Series

76055

Application

Conventional, Mezzanine

Application Tooling Documents

TM-622018799

Component Type

PCB Header

Overview

Impact™ Backplane Connectors and Cable Assemblies

Product Name

Impact™

UPC

883906411558

Physical

Circuits (Loaded)

150

Circuits (maximum)

150

Color - Resin

Black

Durability (mating cycles max)

200

First Mate / Last Break

No

Flammability

94V-0

Guide to Mating Part

No

Keying to Mating Part

None

Material - Metal

High Performance Alloy (HPA)

Material - Plating Mating

Gold

Material - Plating Termination

Tin

Material - Resin

High Temperature Thermoplastic

Net Weight

3.897/g

Number of Columns

10

Number of Pairs

5

Number of Rows

15

Orientation

Vertical

PC Tail Length

1.40mm

PCB Locator

No

PCB Retention

None

PCB Thickness - Recommended

1.00mm

Packaging Type

Tray

Pitch - Mating Interface

1.90mm

Pitch - Termination Interface

1.90mm

Plating min - Mating

0.762µm

Polarized to PCB

No

Stackable

No


Temperature Range - Operating

-55°C to +85°C

Termination Interface: Style

Through Hole - Compliant Pin

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Not Contained Per

-ED/79/2015 (17

December 2015)

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com

Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

76055 Series

Mates With

76060 Impact™ 100 Ohm Daughtercard

Use With

75234 Backplane Free Standing Guide Pin

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Backplane Header

0621009610

Removal Tool for

GbX® U-Series, GbX

Current - Maximum per Contact	0.75A	I-Trac™, Impact™, or Z-PACK Tinman*
Data Rate	25.0 Gbps	Backplane Insertion <u>0621005800</u>
Impedance	100#	Tool for Signal
Shield Type	N/A	Contact
Shielded	No	Press-In Tool for <u>0622018658</u>
Voltage - Maximum	30V AC (RMS)/DC	Backplane Module
Solder Process Data		
Lead-freeProcess Capability	N/A	
Material Info		
Reference - Drawing Numbers		
Application Specification	AS-76060-990, AS-76060-9999	
Product Specification	PS-76060-999	
Sales Drawing	RSD-173430-001, SD-76055-001	
Symbol/Footprint Data	SYM-76055-1125	

This document was generated on 02/29/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION