

		2		3		4		5		6		7		8	
△ ALTW CONFIDENTIAL 2019-02-25 R&D DEPT.		REV.		ECN NO.		DATE		SIGN		DESCRIPTION					
		C		LEN-8B0522		2008/09/17		Shin		Add Note					
		D		LEN1590277		2015/09/01		Vicky		Update Logo					
		E		CI90273		2019/02/25		Ruru		Modify Note					
△ MLTV ALTW 20.6		△ 18.0 △ 4.0 △ 1.8 1.5 15.45 ± 0.25 5/8"-27UNS 20.3		△ ALTW 7 1 2 3 4 6 23.8 (REF.)											
△ MLTV ALTW 1 2 3 4 5 6 7 Pin Assignments Front View		△ 15.6 ± 0.1 14.8 ± 0.1 Recommended Panel Cut-out		14.5 With Liquid Glue Connector ① Nut ② Gasket ③		Note: △ * ∅ Important Dimension To Check. * Waterproof Rate: IP67, Unmated * Housing: Thermoplastic, Black * Pin: Copper Alloy, Gold Plated * Nut: Thermoplastic, Black * Gasket: Rubber, Black △ * Use With Waterproof Cap Or Dust Cap Panel Thickness Max: 3.0mm △ * Use Without Waterproof Cap Or Dust Cap Panel Thickness Max: 4.0mm * Gasket and Nut are packed separately in PE bags.									
UNIT:mm ⌀ ⌀ TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		TITLE Standard Panel Screw 7Pin M Conn M Pin SCALE 2:1 SIZE A4 SHEET 1 OF 1 REV. E WC-REV. A.3 ∅ Inspection item		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO BD-07PMMS-SC7001 DWG NO BD-07PMMS-SC7001 CUSTOMER ALTW		DRAWN BY Ruru CHECKED BY Rita APPROVED BY Max		DATE 2019-02-25 DATE 2019-02-25 DATE 2019-02-25					
		2		3		4		5		6		7		8	

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.