XZCC20FCM30B









Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector 1/2 20 UNF, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <= 0.75 mm ² / clamping capacity 0.120.24 in (36 mm)

Complementary

Cable gland type	Pg 7
Cable connector fixing	Screw-on
System Voltage	250 V AC
Line Rated Current	4 A
Enclosure material	Plastic
Insulating resistance	> 1000 GΩ
Contact resistance	<= 8000 μOhm
Product weight	0.04 lb(US) (0.02 kg)

Environment

IP degree of protection	IP67	contai
ambient air temperature for operation	-40185 °F (-4085 °C)	- ston


Offer Sustainability

Not Green Premium product	Not Green Premium product	
Compliant - since 0545 - Schneider Electric declaration of conformity	Compliant - since 0545 - Schneider Electric declaration of conformity	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Connections and Schemes

