

f	6	6	6	6	6	6	6	6	6	6				6	6	6	6	6	6	6	6	6	6	6							
e	4	4	4	4	4	4	4	4	4	4				4	5	4	4	4	4	4	4	4	4	4							
d	4	4	4	4	4	4	6	4	4	4				4	5	4	4	4	6	4	6	4	6	4							
c	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	4	6	4	4	6							
b	4	4	5	4	4	4	4	4	4	5				4	4	4	4	4	5	4	4	4	5	4							
a	4	4	4	4	4	4	4	4	4	4				4	4	5	4	4	4	4	5	4	4	4							
z	6	6	6	6	6	6	6	6	6	6				6	6	6	6	6	6	6	6	6	6	6							
P O S	0						0						1						1						2						2
	1						5						0						5						0						5

EXAMPLE)

The drawing shows two elevations of a building facade. The top elevation is a side view with a total width of 50.0 MAX and a height of 12.00. It features a central entrance and two wings of windows. The bottom elevation is a front view with a total width of 50.0 MAX and a height of 13.45 +0.15 / -0.10. It shows a central entrance flanked by two wings of windows. Dimensions for the bottom elevation include 3.00 +0 / -0.10 for the base height, 15.40 ± 0.50 for the total width, 11.70 ± 0.10 for the width of the central entrance, and 2.00 ± 0.05 (10x) for the width of the window units. Notes 3, 5, and 6 are present.

12.00

50.0 MAX

15.40±0.50

11.70±0.10

NOTE 3

NOTE 6

13.45+0.15
-0.10

3.00+0
-0.10

2.00±0.05(6x)

NOTE 5

2.00±0.05 (10x)

20.00

2.00±0.05 (10x)

20.00

Diagram illustrating the dimensions of three different connector types (4, 5, and 6) relative to a seating plane for the connector.

The dimensions are defined as follows:

- Connector 4:** The distance from the seating plane to the center of the connector is 8.20. The distance from the seating plane to the tip of the connector is 3.70.
- Connector 5:** The distance from the seating plane to the center of the connector is 9.70. The distance from the seating plane to the tip of the connector is 3.70.
- Connector 6:** The distance from the seating plane to the center of the connector is 11.20. The distance from the seating plane to the tip of the connector is 3.70.

[illegible]

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P07PDN131----

[illegible]