


- Multiple sizes, strengths, and mounting options anchor Nytyes® securely.
- Five Types:
 - 1) Flat Adhesive-Back and Screw Mounts
 - 2) Saddle Screw Mount only
 - 3) Push Mount Arrowhead and **Blind Mounts**
 - 4) Snap Over Bolt
 - 5) Stainless Steel Clip
- Rubber based adhesive effective up to 126°F (52°C).
- Apply Adhesive-Backed parts to a clean, dry surface.



	MAX. TENSILE STRENGTH Lbs. N		INSERT POINTS	in. mm.		PART NO. Black	DESCRIPTION	PA A in. mm.			RT DIMENSION B in. mm.		NS C in. mm.	
NEW!	50	222	2	#10 1/4	5,0 6,0	3706 3707	MP S-M5* MP S-M6	.96	24,4	.60	15,2	.32	8,1	
	120	534	2	1/2 9/16 5/8	12,0 14,0 16,0	3710 3711 3754	MP S-1/2 MP S-9/16 MP S-5/8	2.31	58,7	1.25	31,8	1.05	26,7	

Standard color black.

^{*3706} will also work with the PEM X-Press 5 mm stud








Stainless Steel Edge Clip Platforms

ALL NEW PRODUCTS

	CABLE /IDTH*	PANEL TICKNESS RANGE Minimum Maximm				INSERT POINTS	PART NO.	DESCRIPTION	PART DIMENSION				NS	IS C	
in.	mm.	in.	mm.	in.	mm.	TOINTO	NO.		in.	mm.	in.	mm.	in.	mm.	
.31	8.0	.06	1,5	.12	3,0	4	S6474	SunRunner CT	1.03	26,2	.63	16,0	.77	19,5	
.01	0,0	.12	3,0	.25	6,4	4	S6475	SunRunner CT-EZ							

^{*}Edge Clip Platforms SunRunner CT and CT-EZ fit all Heyco Stainless Steel Cable Ties, see page 7-69





Material

Nylon 6/6 (Snap Over Bolts)

.025" Thick 304 stainless steel (CT & CT-EZ)

Certifications



 $_{c}(U_{L})_{us}$ Certified by UL for Compliance with both Canadian and US Requirements under File E54523 (CT & CT-EZ)