

5

4

3

2

1

Lieferumfang :

1 Gehäuse mit Deckel-Zinkdruckguss

2 Rändelschrauben :

4-40 UNC x 16,9 (bei X=0)

M3 x 16,9 (bei X=3)

2 Zylinderschrauben mit Innensechskant :

4-40 UNC x 17,5 (bei X=2)

M3 x 17,5 (bei X=1)

2 Federringe 2,6 DIN 127 B (bei X=1 oder 2)

1 Erdungsschraube M2,5 x 4

4 Deckelschrauben M2,5 x 6,5

Bei Verwendung eines Schraubendrehers mit Kugelkopf wird die Bedienbarkeit der Schrauben wesentlich vereinfacht

Bestellnummer : 61 03 600 0021

Hood assembly consists of :

1 Metal hood with cover-diecast zinc

2 Thumb screws (knurled) :

4-40 UNC x 16,9 (with X=0)

M3 x 16,9 (with X=3)

2 Cylinder socket head cap screws :



4-40 UNC x 17,5 (with X=2)

M3 x 17,5 (with X=1)

2 Spring washers 2,6 DIN 127 B (with X=1 or 2)

1 Screw M2,5 x 4 for grounding post

4 Cover screws M2,5 x 6,5



X = 0 ... 3

				Dat.	Name		INDUCOM	Maßstab/ Scale
			Detail.	14/08/03	STRAUCH		Full metal hood for D-Sub	1:1
			Insp.				37 poles connectors with	
			Stand.				angled/straight cable entry	
								Blatt/ Page
32473	10/01/05	STRAUCH					TB 61 03 001 X018	1 / 1
Mod.	Dat.	Name					Sub.	

HARTING Electronics GmbH & Co. KG
D-32339 ESPELKAMP

