## Product datasheet **Characteristics**

# **ZCY54**





Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch lever
Device short name	ZCY
Product compatibility	XCKD XCKP XCKT XCMD
Associated head	ZCE01 ZCE05
Movement of operating head	Rotary
Type of operator	Rod lever spring return metal (square rod 3 mm, L = 125 mm)
Tracks	No track
Type of approach	Lateral approach

### Complementary

Switch actuation	By any moving part
Positive opening	Without

#### **Environment**

ambient air temperature for operation	-13158 °F (-2570 °C)	
ambient air temperature for storage	-40158 °F (-4070 °C)	
environmental characteristic	Standard environment	

#### **Offer Sustainability**

Green Premium product	Green Premium product
Compliant - since 0851 - Schneider Electric declaration of conformity	Compliant - since 0851 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.	
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period

18 months

