

10135313 - 10X LF

LEAD-FREE DESIGNATION
ONLY WITH APPLICABLE
PLATING CODES

SEE NOTE 2

MODULE
DESCRIPTION

LETTER DESIGNATION REPRESENTED IN DASH NUMBER

BASE
MODULE

LEFT
POLARIZING
GUIDANCE
MODULE
(SEE SHEET 3)

N

J
(NO KEY)

A

B

C

D











E

F

G

H

NO KEY
NO GUIDE PIN



RIGHT
POLARIZING
GUIDANCE
MODULE
(SEE SHEET 2)

Z

Y
(NO KEY)

P

Q

R

S











T

U

V

W

NO KEY
NO GUIDE PIN




NO TOOLED

PRELIMINARY



spec ref	---	dr	Jackie Chen	2015/05/19	projection	MM	size	A2	scale	8:1
tolerance std	ASME Y14.5M	eng	Jackie Chen	2016/03/15	chr	-	ecn no	-		
		appr	-	-	product family	AirMax VS2	rel level	Preliminary		
surface	-	linear	0.X	±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 5 PAIR, 120 POS, 8 IMLA, 20MM, W/GUIDE/KEY	dwg no	10135313	rev
			0.XX	±.15						
			0.XXX	±.050						
		angular	0°	±°		cat. no.	-	Product - Customer Drw	sheet 1 of 4	

Amphenol
FCI

© 2016 APCI





LEFT POLARIZATION WITH GUIDE



RECOMMENDED PCB LAYOUT

ODD COLUMN, CONTACT ROW ID



PRELIMINARY


spec ref	---	dr	Jackie Chen	2015/05/19	projection	MM	size	A2	scale	8:1
tolerance std	ASME Y14.5M	eng	Jackie Chen	2016/03/15	chr	-	ecn no	-		
		appr	-	-	product family	AIRMAX VS2	rel level	Preliminary		
surface	-	linear	0.X	±.3	Amphenol FCI	title	AIRMAX VS2 R.A. RECEPTACLE	dwg no	10135313	rev
			0.XX	±.15						
			0.XXX	±.050						
		angular	0°	±°	cat. no.	-	Product - Customer Drw	sheet 3 of 4		

PRODUCT NUMBER	PRESS-FIT TAIL PLATING TYPE
10135313-10*LF	TIN OVER NICKEL (LEAD FREE)


- 1 - CONNECTOR MATERIALS:
HOUSING: HIGH TEMP THERMOPLASTIC, NATURAL, UL94-V0
IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0
CONTACT: COPPER ALLOY
ORGANIZER: HIGH TEMP THERMOPLASTIC, WHITE, UL94-V0
- 2 - CONTACT PLATING:
SEPARABLE INTERFACE:
PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE
REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-0956
INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995)
CENTRAL OFFICE TEST SEQUENCE

PRESS-FIT TAILS: SEE TABLE


- 3 - PRODUCT SPECIFICATION: GS-12-0956
- 4 - APPLICATION SPECIFICATION: GS-20-0305.
- 5 - PRODUCT MARKING, (PART NUMBER & LOT CODE), ON THIS SURFACE.
- 6 - THE MINIMUM CENTERLINE SPACING BETWEEN ADJACENT
MODULES IS 24.0 MM.
- 7 - CONNECTOR OUTLINE MAY BE SCREEN PRINTED ONTO CUSTOMER PCB TO
BE USED AS A GUIDE FOR MANUAL CONNECTOR PLACEMENT.
- 8 - REFER TO CUSTOMER DRAWING 10104444 FOR INFORMATION
ON PCB HOLE DIAMETERS AND PLATING OPTIONS
- 9 - LEAD FREE PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES &
OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- 10 - PACKAGING MEETS GS-14-920 LEAD FREE LABELING
SPECIFICATION.
- 11 - GROUND CONTACTS (C,F, AND I IN ODD COLUMNS AND A, D, AND G,
EVEN COLUMNS) REQUIRE (Ø0.500) FINISHED HOLES. SIGNAL LOCATIONS
REQUIRE (Ø0.400) FINISHED HOLES.
- 12 - THESE OUTER VIAS (M) ARE OPTIONAL. WHILE NO CONNECTOR EONS ARE
PRESSED INTO THESE HOLES WE RECCOMEND (Ø0.500) FINISHED HOLES
AT THESE LOCATIONS TO PROVIDE GROUND SYMMETRY THROUGH THE PCB.
- 13 - A  SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE, WHICH
HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION
- 14 - CUSTOMER CAN FIX THE CONNECTOR WITH THREAD FORMING SCREW THROUGH
THIS PTH. THE SCREW IS #2-32, THE VALID LENGTH OF SCREW IS 4.5MM PLUS THE
THICKNESS OF PCB.



DETAIL A
SCALE 20:1



10135313-10ALF



10135313-10PLF

spec ref	---	dr	Jackie Chen	2015/05/19	projection	MM	size	A2	scale	4:1
tolerance std	ASME Y14.5M	eng	Jackie Chen	2016/03/15	chr	-	ecn no	-		
	TOLERANCES UNLESS OTHERWISE SPECIFIED	appr	-	-	product family	AirMax VS2	rel level	Preliminary		
surface	-	linear	0.X	±.3	Amphenol FCi	title	AIRMAX VS2 R.A. RECEPTACLE ASS'Y, 5 PAIR, 120 POS, 8 IMLA, 20MM, W/GUIDE/KEY	dwg no	10135313	rev
			0.XX	±.15						
			0.XXX	±.050						
		angular	0°	±°		cat. no.	-	Product - Customer Drw	sheet 4 of 4	