


# Series 12X Shortstop Circuit Breakers



## Auto, Manual & Modified Reset Circuit Breakers

### Specifications

#### Single Pole Thermal Type Breakers

**Applications:** Battery chargers, trucks, buses, RVs, trolling motors, etc

**Rating:** 5-50A, 14Vdc; 28Vdc (Series 123, 124, & 125)

**Interrupt Rating:** Main Circuit Protection: 1.5kA @ 12Vdc (Series 123 w/plastic cover);

**Branch Circuit Protection:** 2.5kA @ 12Vdc (Series 121 & 124 -01 sealed & Series 123 w/plastic cover)

**Operating Temperature Rating:** -40°F (-40°C) to 185°F (85°C)

**Storage Temperature Rating:** -40°F (-40°C) to 260°F (125°C)

**Materials:** Black UL-Rated thermoplastic body (thermoset for Type II body & buttons). Cover is grey thermoplastic or steel-Type I gold, Type II silver

**Marking:** Custom marking available. Consult factory for options

**Termination:** #10-32 thread and quick-connect options available


**Torque Rating:** 24 in-lbs (2.7N•m) max

**Mounting Torque Rating:** Plastic cover - 15 in-lbs (1.7N•m); Metal cover - 30 in-lbs (3.4N•m)





**Ingress Protection Rating:** IP66 On plastic cover version only (except for terminals)

**Compliances:** SAE J553; SAE J1171 (ignition protected)


### Terminal Options



### Cover & Bracket Options



### Hardware



### Part Numbering System

Series	Terminal	Rating	Bracket	Mtg. Holes	Cover*	Options	Hardware
1 2 3							
121 - Type I, 12 VDC	A - Two 10-32 studs; .66 (Aux), .56 (Bat)	05 - 5 amps 08 - 8 amps	0 - No bracket A - Bracket	0 - No bracket 1 - .140 dia. 2 - .196 dia.	M - Metal* P - Plastic*	01 - Waterproof (metal covers only) 02 - Splashproof (optional on metal covers - add 02 suffix; std. on plastic covers - omit 02 suffix.)	WA - Whiz-lock nut assembled WB - Whiz-lock nut bulk
122 - Type II, 12 VDC	B - Two 10-32 studs; .56 (Aux & Bat)	12 - 12 amps	C - Bracket	3 - .237 dia.			HA - Nut & lock washer assembled
123 - Type III, 24 VDC	C - Two 10-32 studs; .66 (Aux & Bat)	15 - 15 amps 20 - 20 amps	E - Bracket (plastic only)	4 - .265 dia. (metal only) 5 - .228 dia. (plastic only)			HB - Nut & lock washer bulk
124 - Type I, 24 VDC	***D - Two .250 QC; (Aux & Bat)	25 - 25 amps 30 - 30 amps		6 - .221 dia. (metal only)			KA - Keps lock nut assembled
125 - Type II, 24 VDC	**H - One 10-32 stud .56 (Bat), Double .250 QC (Aux)	35 - 35 amps 40 - 40 amps 50 - 50 amps					KB - Keps lock nut bulk
	L - Two 10-32 studs; .37 (Aux & Bat)						

\*Series 123 available in plastic cover only. Series 122 & 125 available in metal cover only. \*\*40A maximum \*\*\*30A maximum