



CONTACT LAYOUT

4805 (3/11)

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

By

ALL RIGHTS RESERVED.

LOC

DIST

AD

00

REV

LTR

DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1

—

—

—

1

MATERIAL:

CONTACT: PHOSPHOR BRONZE.

HOUSING: GLASS-FILLED POLYESTER.

2

GENERAL PLATING SPECIFICATION: UNDERPLATING

(ENTIRE CONTACT): 1.27μm MIN NICKEL AND ACTION

PIN: 0.5μm MIN TIN.

FOR PLATING OF MATING SURFACES SEE APPLICABLE

SPECIFICATION REFERENCE FOR EACH DASH NUMBER.

3

CONFORMS TO ALL TESTING ACCORDING TO IEC 61076-4-101

PERFORMANCE LEVEL 2.

4

CONFORMS TO ALL TESTING ACCORDING TO IEC 61076-4-101

PERFORMANCE LEVEL 1.

5

CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL 3,

CENTRAL OFFICE APPLICATIONS.

6

CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL 3,

UNCONTROLLED ENVIROMENT APPLICATIONS.

7

CONNECTOR MARKED WITH PART NUMBER AND DATE CODE.

ADDITIONAL CHARACTERS OR MARKINGS, AS WELL AS THE LOCATION OF THE MARKINGS,

MAY BE ADDED FOR TRACEABILITY BASED UPON MANUFACTURERS DISCRETION.

8

PLATED-THROUGH HOLES AT 2x2mm SQUARE GRID

PATTERN DEFINED BY CONTACT LAYOUT.

9

FOR ACTUAL PIN LOADING SEE "CONTACT LAYOUT".

10

FOR ACTUAL PIN DIMENSIONS SEE "CONTACT DIMENSIONS".

11

AREA RESERVED FOR KEYING PART (BASIC P/N 100525)

12

POLARIZATION FEATURE.

13

TO BE MEASURED AT BOTTOM OF SHROUD.

14

CONNECTOR LUBRICATED WITH BELCORE APPROVED LUBRICANT,

TECHNICAL REFERENCE: TR-NWT-001217 ISSUE 1, SEP 1992.

15

0.76μm MIN GOLD PLATING ON MATING SURFACE.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

B CARBO

26JUL05

CHK

G SKIPPER

26JUL05

APVD

G SKIPPER

26JUL05

NAME

MALE ASSEMBLY, Z-PACK 2mm HM,

TYPE A

SIZE

A1

CAGE CODE

00779

DRAWING NO

5352332

RESTRICTED TO

—

DIMENSIONS:

mm

0-PLC

1-PLC

2-PLC

3-PLC

4-PLC

ANGLES

±

± 0.1

±

±

±

±

±0.2

TOLERANCES UNLESS OTHERWISE SPECIFIED:

±0.2

DIMENSIONS:

mm

0-PLC

1-PLC

2-PLC

3-PLC

4-PLC

ANGLES

±

± 0.1

±

±

±

±

±0.2

TOLERANCES UNLESS OTHERWISE SPECIFIED:

±0.2

MATERIAL

SEE SHEET 1

FINISH

SEE SHEET 1

WEIGHT

—

CUSTOMER DRAWING

SCALE

4:1

SHEET

2

OF

2

REV

C

4805 (3/11)