

Han 1A-2+PE-s-f



Part number	09 10 002 2705
Specification	Han 1A-2+PE-s-f
HARTING eCatalogue	https://b2b.harting.com/09100022705

Identification

Category	Inserts
Series	Han [®] 1 A

Version

Termination method	Screw termination
Gender	Female
Locking type	Single locking lever
Size	1 A
Number of contacts	2
PE contact	Yes
Details	Order separately the single wire seal or the hoods/housings for an IP65 performance. Please order locking lever separately.

Technical characteristics

Conductor cross-section	0.75 ... 1.5 mm ²
Rated current	10 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	≥10 ⁸ Ω
Limiting temperature	-30 ... +90 °C
Tightening torque	0.25 Nm
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP20

Material properties

Material (insert)	Polyamide
-------------------	-----------



Pushing Performance

Material properties

Colour (insert)	RAL 9005 (jet black)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (seal)	NBR
Colour (seal)	Black
Material flammability class acc. to UL 94	V-0

Specifications and approvals

Specifications	EN 45545-2 R22: HL1, HL2, HL3
	EN 45545-2 R23: HL1, HL2, HL3
	EN 45545-2 R24: HL1, HL2, HL3
	EN 61373 Cat 1B

Commercial data

Packaging size	1
eCl@ss	27440205 Contact insert for industrial connectors