XZCPV1340L10



Main		
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Pre-wired connectors	
Series name	General purpose	

Complementary

Electrical connection	M12, 3 pins elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	2 PNP LEDs	
Cable length	32.81 ft (10 m)	
Cable outer diameter	0.18 in (4.6 mm)	
Cable composition	3 x 0.25 mm²	
Wire insulation material	PVC	
System Voltage	30 V AC 36 V DC	
Line Rated Current	3 A	
Contact resistance	5000 µOhm	
Insulating resistance	1 GΩ	
Product weight	0.84 lb(US) (0.38 kg)	
Environment		
IP degree of protection	IP65 IP67	
product certifications	CULus	
ambient air temperature for operation	-13176 °F (-2580 °C) (static)	
ambient air temperature for storage	-13176 °F (-2580 °C)	

Offer Sustainability


Not Green Premium product	Not Green Premium product	
Compliant - since 1201 - Schneider Electric declaration of conformity	Compliant - since 1201 - Schneider Electric declaration of conformity	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

Contractual warranty

18 months




Dimensions



- L: Lenght of cable
- (1) 2 LEDs limited to 10...30 VDC max.

Connections and Schemes

Connector




BU : Blue BN : Brown

BK : Black

Connections and Schemes

LED Connection



- BN : Brown
- BK : Black
- BU : Blue
- GN : Green
- YW : Yellow
- (1) Signal

