



Pos.	A	B	C	D	E	ØF	G <sup>+0.2</sup>	H	Part NO. Bulk package	Part NO. Single package
9	31.7	25.0	30.0	32.7	15.0	5.0	9.0	9.0	165X17359X	165X17359XE
15	40.0	33.3	32.0	34.7	15.0	5.0	9.0	9.0	165X17369X	165X17369XE
25	53.7	47.0	35.0	37.7	15.0	7.0	12.2	10.0	165X17379X	165X17379XE
37	70.2	63.5	41.0	43.7	15.0	7.0	13.5	11.0	165X17389X	165X17389XE
50	67.8	61.1	41.0	43.7	17.7	9.3	15.3	12.7	165X17399X	165X17399XE

G:\RoHS\_Compliant\_gross\_0001.jpg

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

- NOTES:
1. CASE: ZINC DIE CAST; NICKEL PLATED
  2. JACK SCREW: COPPER ALLOY; NICKEL PLATED
  3. CABLE BUSHING: TPE
  4. CABLE STRAIN RELIEF: STEEL; NICKEL PLATED
  5. ATTENUATION FACTOR >60dB BETWEEN 300 MHz AND 900 MHz

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH  
DO NOT ALTER CAD DRAWING BY HAND

tolerance		dim. in mm	
2007	date	name	
drawn	13.11.	Lehmenkühler	
appd.	13.11.	Kühle	
norm			
d-old			
a	Origin		
rev.	description	date	name



scale:	1:1
material:	SEE NOTES
title:	METAL HOOD 9-50pos. EMI / RFI SHIELDING with straight cable exit and jack screws M3
dwg no:	AutoCAD 2006
	DIN-A 4
	sh: 1/1
part no:	SEE TABLE