THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. - PRINTED CABLE PRINTED CABLE -NOTES: 1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS. 2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY. 3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON. 4. TESTED TO EIA/TIA 568-B.3. 5. PATCH CORD ROUTING CONFIGURATION A TO B. 6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF ROHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RÉSTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE. LC CONNECTOR HOUSING KEY CONFIGURATIONS "B" BLACK RED **GREEN KEYED** -LC CONNECTORS — SC DUPLEXING CLIP **ORANGE** YELLOW DARK BLUE LC DUPLEXING CLIP -DUPLEXED WITH SC CONNECTORS A & B DESIGNATIONS FIBER OPTIC PATCH CORD DUPLEX SC TO KEYED LC CONFIGURATION CUSTOMER DRAWING CORP. TINLEY PARK, ILL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. M02779CR\_DC\_00A.prt DIMENSIONAL TOLERANCES ARE: (.XXX) ±.010 (0.3) SCALE NONE THIRD ANGLE (.XX) ±.03 [0.8] ANGLES PART NO. REVIEW DRAWING NUMBERS MC SEE TABLE, SHT. 2 DRAWING NO. SIZE 10-25-07 MC RELEASED TO PRODUCTION 02779-51 10-01-07 02779-51 REV DATE SUP ОТН BY CHK DESCRIPTION ECN - R CUST

MC

BY CHK

RELEASED TO PRODUCTION

DESCRIPTION

10-25-07

DATE

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

DUPLEX SC TO KEYED LC FIBER OPTIC PATCH CORD										
PANDUIT PART NO.	CABLE				SC CONNECTORS			KEYED LC CONNECTORS		
	FIBER TYPE	RATING	COUNT	COLOR	MAX. IL	MIN. RL	COLOR	MAX. IL	MIN. RL	KEY/COLOR
F5E3-10AM** F5E3-10BM** F5E3-10CM** F5E3-10MD** F5E3-10ME** F5E3-10MF**	50/125um OM2	RISER (OFNR)	DUPLEX 1.6mm ZIPCORD	ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	A/BLACK B/RED C/GREEN D/YELLOW E/ORANGE F/DK.BLUE
F6E3-10AM** F6E3-10BM** F6E3-10DM** F6E3-10EM** F6E3-10FM**	62.5/125um OM1	RISER (OFNR)	DUPLEX 1.6mm ZIPCORD	ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	A/BLACK B/RED C/GREEN D/YELLOW E/ORANGE F/DK.BLUE
FXE3-10AM** FXE3-10BM** FXE3-10CM** FXE3-10DM** FXE3-10ME** FXE3-10MF**	10 GbE 50/125um OM3	RISER (OFNR)	DUPLEX 1.6mm ZIPCORD	AQUA	0.30dB	20dB	ELECTRIC IVORY	0.30dB	26dB	A/BLACK B/RED C/GREEN D/YELLOW E/ORANGE F/DK.BLUE
F9E3-10AM** F9E3-10BM** F9E3-10CM** F9E3-10EM** F9E3-10FM**	9/125um OS1	RISER (OFNR)	DUPLEX 1.6mm ZIPCORD	YELLOW	0.75dB	55dB	BLUE	0.35dB	55dB	A/BLACK B/RED C/GREEN D/YELLOW E/ORANGE F/DK.BLUE
** - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET										
						FIBER OPTIC PATCH CORD DUPLEX SC TO KEYED LC CONFIGURATION customer drawing				
						TINLEY PARK, ILL 60477				
						ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (I.X)  THIRD ANGLE (I.XXX):.010 [0.3]  CRAWN BY REVIEW DRAWING NUMBERS  PART NO.				



SUP

02779-51

ECN - R

DRAWN BY MC

10-01-07

REVIEW DRAWING NUMBERS

AS NOTED

SEE TABLE

02779-51

(SHT. 2 of 2)

SIZE

DRAWING NO.