SOURIAU

# The full plastic circular connector

## UTP provides the complete answer to the need for economical lightweight and robust circular connector

| | |
|---|---|
| **Flammability rating** | UL94-V0 compliant |
| **Rapid and secure locking** | Locks with audible positive «click» |
| **Interconnectivité & intermariable** | Intermateable and interchangeable with UTO, UTG and UTS Series |
| **Complete range of contacts** | Trim Trio contacts #16 |

Esterline
Connection Technologies

## Layout

| Shell size | Contact # 16 (Ø 1,6) | Mixed power / signal versions |
|---|---|---|
| **10** |  10-4 |  10-3<br>3 x #16 (Ø 1,6)<br>Group C 250V |
| **12** |  12-8 |  12-2G1 |
| **14** |  14-12 | |
| **16** |  16-19 | |
| **18** |  18-23 |  18-7<br>Group C 380V<br>7 x # 16 (Ø 1,6) |

| Shell size | Contact # 16 (Ø 1,6) | Mixed power / signal versions |
|---|---|---|
| **20** |  20-28 | |
| **22** |  22-35 | |
| **24** |  24-48 | |

Contact identification positions shown are for mating face of pin contact connectors and wire face of socket contact connectors.




## Specifications

| Connector type | Shell size | Contacts number* | Part number | |
|---|---|---|---|---|
| | | | Male insert | Female insert |
| Cable plug | 10 | 4 | UTP6104P | UTP6104S |
| | | | UTP6103P | UTP6103S |
| | 12 | 8 | UTP6128P | UTP6128S |
| | | 2 + ground | UTP6122G1P | UTP6122G1S |
| | 14 | 12 | UTP61412P | UTP61412S |
| | 16 | 19 | UTP61619P | UTP61619S |
| | 18 | 23 | UTP61823P | UTP61823S |
| | | 6 + ground | UTP6187P | UTP6187S |
| | 20 | 28 | UTP62028P | UTP62028S |
| | 22 | 35 | UTP62235P | UTP62235S |
| | 24 | 48 | UTP62448P | UTP62448S |
| Panel mounting receptacle | 10 | 4 | UTP0104P | UTP0104S |
| | | | UTP0103P | UTP0103S |
| | 12 | 8 | UTP0128P | UTP0128S |
| | | 2 + ground | UTP0122G1P | UTP0122G1S |
| | 14 | 12 | UTP01412P | UTP01412S |
| | 16 | 19 | UTP01619P | UTP01619S |
| | 18 | 23 | UTP01823P | UTP01823S |
| | | 6 + ground | UTP0187P | UTP0187S |
| | 20 | 28 | UTP02028P | UTP02028S |
| | 22 | 35 | UTP02235P | UTP02235S |
| | 24 | 48 | UTP02448P | UTP02448S |

*Contacts supply separately

# Dimensions

## Cable Plug - UTP6







| Shell size | ØA±0.2 | B max | | ØC±0.15 | ØD±0.15 | ØE±0.2 |
|---|---|---|---|---|---|---|
| | | Pin contact | Socket contact | | | |
| 10 | 26.7 | 31.8 | 23.9 / 26.75 | 10.9 | 12.2 | 19.1 |
| 12 | 31.4 | | 23.9 | 13.8 | 15.1 | |
| 14 | 34.5 | | | 17.0 | 18.3 | |
| 16 | 37.8 | | | 19.9 | 21.5 | |
| 18 | 40.8 | 31.8 / 33.0 | 23.9 / 29.0 | 22.4 | 24.0 | |
| 20 | 43.9 | 31.8 | 24.9 | 25.6 | 27.2 | |
| 22 | 47.0 | | | 28.5 | 30.4 | |
| 24 | 50.1 | | 26.2 | 31.7 | 33.5 | |

## Panel Mounting - UTP0










| Shell size | A max | | B±0.15 | C±0.2 | ØD±0.15 | ØE±0.2 | F±0.25 | ØG±0.1 | ØJ±0.1 |
|---|---|---|---|---|---|---|---|---|---|
| | Pin contact | Socket contact | | | | | | | |
| 10 | 31.7 | 24.3 / 27.6 | 2.3 | 11.3 | 15.0 | 18.3 | 23.8 | 3.2 | 15.1 |
| 12 | | 24.3 | | | 19.0 | 20.6 | 26.2 | | 18.2 |
| 14 | | | | | 22.2 | 23.0 | 28.6 | | 21.4 |
| 16 | | | | | 25.3 | 24.6 | 31.0 | | 24.6 |
| 18 | 31.7 / 34.0 | 24.3 / 30.4 | 2.5 | 11.3 / 17.9 | 28.5 | 27.0 | 33.3 | | 27.7 |
| 20 | 33.3 | 27.0 | | 14.5 | 31.7 | 29.4 | 36.5 | | 30.9 |
| 22 | | 28.0 | 3.5 | | 34.9 | 31.8 | 39.7 | | 34.1 |
| 24 | | 30.4 | | 15.3 | 38.0 | 34.9 | 42.9 | 3.9 | 37.3 |

Note: all dimensions are in mm

# Accessories and tooling

## Cable Clamp

| Part number | Shell size |
|---|---|
| UTG10AC | 10 |
| UTG12AC | 12 |
| UTG14AC | 14 |
| UTG16AC | 16 |
| UTG18AC | 18 |
| UTG20AC | 20 |
| UTG22AC | 22 |
| UTG24AC | 24 |

## Cable Clamp for Waterprotected (IP65) Applications

| Part number | Shell size |
|---|---|
| UTG10PG | 10 |
| UTG12PG | 12 |
| UTG14PG | 14 |
| UTG16PG | 16 |
| UTG18PG | 18 |
| UTG20PG | 20 |
| UTG22PG | 22 |
| UTG24PG | 24 |

## Cable Gland for Waterprotected (IP65) Applications

| Part number | Shell size |
|---|---|
| UTG10ST | 10 |
| UTG12ST | 12 |
| UTG14ST | 14 |
| UTG16ST | 16 |
| UTG18ST | 18 |
| UTG20ST | 20 |
| UTG22ST | 22 |
| UTG24ST | 24 |

## Metal Shrink Boot

| Part number | Shell size |
|---|---|
| UTG10AD | 10 |
| UTG12AD | 12 |
| UTG14AD | 14 |
| UTG16AD | 16 |
| UTG18AD | 18 |
| UTG20AD | 20 |
| UTG22AD | 22 |
| UTG24AD | 24 |

## Dustcap (Receptacle)

| Part number | Shell size |
|---|---|
| UTP10DC | 10 |
| UTP12DC | 12 |
| UTP14DC | 14 |
| UTP16DC | 16 |
| UTP18DC | 18 |
| UTP20DC | 20 |
| UTP22DC | 22 |
| UTP24DC | 24 |

## Dustcap with Chain (Receptacle)

| Part number | Shell size |
|---|---|
| UTP10DCG | 10 |
| UTP12DCG | 12 |
| UTP14DCG | 14 |
| UTP16DCG | 16 |
| UTP18DCG | 18 |
| UTP20DCG | 20 |
| UTP22DCG | 22 |
| UTP24DCG | 24 |

## Plastic Protective Cap for Receptacle

| Part number | Shell size |
|---|---|
| 8500-5586A | 10 |
| 8500-5587A | 12 |
| 8500-5588A | 14 |
| 8500-5589A | 16 |
| 8500-5590A | 18 |
| 8500-5591A | 20 |
| 8500-5592A | 22 |
| 8500-5593A | 24 |

## Gasket

| Part number | Shell size |
|---|---|
| UTFD12B | 10 |
| UTFD13B | 12 |
| UTFD14B | 14 |
| UTFD15B | 16 |
| UTFD16B | 18 |
| UTFD17B | 20 |
| UTFD18B | 22 |
| UTFD19B | 24 |

## Handle

| Part number |
|---|
| SHANDLES |

## Tool Kit

| Part number |
|---|
| TOOLKIT |

## Crimp Tooling

| Contacts | Contact size | Part number of head |
|---|---|---|
| RM/RC 28M1K(1) | Standard contacts<br>#16<br>Ø 1.6mm | S16RCM20* |
| RM/RC 24M9K(1) | | S16RCM20* |
| RM/RC 20M13K(1) | | S16RCM20* |
| RM/RC 20M12K(1) | | S16RCM20* |
| RM/RC 16M23K(1) | | S16RCM16* |
| RM/RC 14M30K(1) | | S16RCM14* |
| SM/SC 24ML1TK6(1) | | S16SCM20* |
| SM/SC 20ML1TK6(1) | | S16SCM20* |
| SM/SC 16ML1TK6(1) | | S16SCML1* |
| SM/SC 14ML1TK6(1) | | S16SCML1* |
| SM/SC 16ML11TK6(1) | | S16SCML11* |
| RMDXK10D28K | Coaxial contacts | M10S-1J with die set & stop bushing |
| RCDXK1D28K | | |
| RM/RC DX60xxD28K | | |
| RM/RC DXK10D28 + york090 | | |
| RM/RC DX60xxD28 | | |

(1): example of plating, for other plating contact us

* Heads to be used with Handle PN: SHANDLES

SOURIAU

souriau-industrial.com

contactindustry@souriau.com

Esterline
Connection Technologies

WPNUTPEUSEN01 © Copyright SOURIAU 2014 - All information in this document presents only general particulars and shall not form part of any contract. All rights reserved to SOURIAU for changes without prior notification or public announcement. Any duplication is prohibited, unless approved in writing.