

SPRING-LOADED CONNECTORS

SERIES 419, 430 • .100" GRID TARGET CONNECTORS FOR SPRING-LOADED ASSEMBLIES • DOUBLE ROW STRIPS




FIG. 1




FIG. 2




FIG. 3





FIG. 4

- Series 419 and 430 Spring Target Connectors, supplied in double row strips. Available in through-hole and wire termination configurations
- Target Connectors provide an excellent gold-plated conductive mating surface for spring loaded connectors. These series are offered with a flat face for making contact with our standard .042" dia. spring pin plungers
- Target connectors use MM #1938, #1940, #1942 and #3024 pins. See page 218 for details
- Insulators are high temperature thermoplastic



ORDERING INFORMATION

FIG. 1	Series 419...001	Standard Solder Tails
	419-10-2	-00-001000 Specify number of pins 04-64
FIG. 2	Series 419...002	Long Solder Tails
	419-10-2	-00-002000 Specify number of pins 04-64
FIG. 3	Series 419...005	Elevated with Solder Tails
	419-10-2	-00-005000 Specify number of pins 04-64
FIG. 4	Series 430...240	Solder Cups
	430-10-2	-00-240000 Specify number of pins 04-64
RoHS-2 2011/65/EU XX=Plating Code See Below For Electrical, Mechanical & Environmental Data, See page 264		
SPECIFY PLATING CODE XX=		
Pin Plating	10 μ" Au	