

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0757840240

Status:

Active

Overview:

iPass™ Connector System

Description:

0.80mm Pitch, iPass™ I/O Surface Mount Receptacle, Vertical, Internal Assembly with Shell, 50 Circuit, 0.38µm Gold (Au), Through Hole Option, Tail Length 2.79mm, Universal Key

Documents:

3D Model

Drawing (PDF)

Product Specification PS-75783-001 (PDF)

Application Specification AS-75783-001 (PDF)

RoHS Certificate of Compliance (PDF)

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Agency Certification           |                                                  |
| CSA                            | LR19980                                          |
| UL                             | E29179                                           |
| General                        |                                                  |
| Product Family                 | I/O Connectors                                   |
| Series                         | 75784                                            |
| Application                    | Wire-to-Board                                    |
| Comments                       | Positive or passive latching cable available     |
| Component Type                 | Receptacle                                       |
| Electrical Model               | Yes                                              |
| Overview                       | iPass™ Connector System                          |
| Product Name                   | iPass™, Mini Multi-Lane, PCI Express*            |
| Type                           | N/A                                              |
| UPC                            | 800756840802                                     |
| Physical                       |                                                  |
| Circuits (Loaded)              | 50                                               |
| Circuits (maximum)             | 50                                               |
| Color - Resin                  | Black                                            |
| Durability (mating cycles max) | 50                                               |
| Flammability                   | 94V-0                                            |
| Gender                         | Female                                           |
| Keying to Mating Part          | Yes                                              |
| Lock to Mating Part            | None                                             |
| Material - Metal               | Copper-Nickel-Zinc, High Performance Alloy (HPA) |
| Material - Plating Mating      | Gold                                             |
| Material - Plating Termination | Tin                                              |
| Material - Resin               | High Temperature Thermoplastic                   |
| Net Weight                     | 4.946/g                                          |
| Number of Rows                 | 2                                                |
| Orientation                    | Vertical                                         |
| PC Tail Length                 | 2.79mm                                           |
| PCB Locator                    | Yes                                              |
| PCB Retention                  | Yes                                              |
| PCB Thickness - Recommended    | 2.36mm                                           |
| Packaging Type                 | Embossed Tape on Reel                            |
| Panel Mount                    | No                                               |
| Pitch - Mating Interface       | 0.80mm                                           |
| Pitch - Termination Interface  | 0.80mm                                           |
| Plating min - Mating           | 0.381µm                                          |
| Plating min - Termination      | 2.540µm                                          |
| Polarized to Mating Part       | Yes                                              |
| Ports                          | 1                                                |
| Surface Mount Compatible (SMC) | Yes                                              |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Contains SVHC(2014

December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product

environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)

Please visit the [Contact Us](#) section for any

non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

75784 Series

Use With

iPass™ Cable Assemblies, [79575](#) , [79576](#) , [74562](#) , [74563](#) , [79536](#) , [74573](#) ,

|                                                |                             |
|------------------------------------------------|-----------------------------|
| Temperature Range - Operating                  | -40°C to +80°C              |
| Termination Interface: Style                   | Surface Mount, Through Hole |
| Waterproof / Dustproof                         | No                          |
| Wire Insulation Diameter                       | N/A                         |
| Wire Size AWG                                  | N/A                         |
| <b>Electrical</b>                              |                             |
| Current - Maximum per Contact                  | 0.5A                        |
| Grounding to Panel                             | None                        |
| Voltage - Maximum                              | 30V AC (RMS)/DC             |
| <b>Solder Process Data</b>                     |                             |
| Duration at Max. Process Temperature (seconds) | 020                         |
| Lead-freeProcess Capability                    | REFLOW                      |
| Max. Cycles at Max. Process Temperature        | 001                         |
| Process Temperature max. C                     | 260                         |
| <b>Material Info</b>                           |                             |
| <b>Reference - Drawing Numbers</b>             |                             |
| Application Specification                      | AS-75783-001                |
| Electrical Model Document                      | EE-75577-001                |
| Product Specification                          | PS-75783-001                |
| S-Parameter Model                              | SP-75577-001                |
| Sales Drawing                                  | SD-75784-001                |

This document was generated on 07/06/2015

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION