









P.C.B. HOLE DRILLINGS
(P.C.B. TOP SIDE)



NOTES:

- METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
- INSULATORS: PBT GF UL 94 V-0; BLACK
- CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
☐ PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
☐ PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
☐ PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
- THREADED REAR SPACERS / FRONT THREADED LOCKS:
COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- SLEEVES: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
- CONNECTOR IS PART MARKED: **163□13729X CONEC ABC** (see note 3)



Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH					tolerance		 dim. in mm	scale: 2:1 (5:1)			
								material: see notes			
						date	name		title: D-SUB MALE 9pos. SOLDER PIN STRAIGHT with threaded rear spacer / front threaded lock		
						drawn 27.05.14	Henneboel				
						appd.					
						norm					
						d-old	16K1A657/16K2A657		dwg no: 16K1A3464  part no: 163□13729X (see note 3)		
	2 x b		Ä5226		27.05.2014		K.H.				
	a		Original								
	rev.		description		date		name				

D-SUB MALE
9pos. SOLDER PIN STRAIGHT
with threaded rear spacer / front threaded lock

16K1A3464 (b)

DIN-A3
sh: 1