





PRODUCT NUMBER
SEE TABLE

ONLY FOR LONG
AND SHORT PIN



FOR NO LONG
AND SHORT PIN



mat'l. code NOTES 2 & 3				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family LATCH-N-LOK		
ltr	ecn no	dr	date	tolerances unless otherwise specified					title			
J	ELX-N-008447	ZK	11/29/11	angles	linear	.004±.01/.04±.3			INCH/MM	1X8 LNL RIGHT ANGLE HEADER ASSEMBLY		
K	ELX-N-23471	MZ	03/15/16			.000±.005/.004±.13						
				0°±2°		.000±.002/.000±.051			scale 1:1			
				dr	J. LINN	7/17/90	Amphenol FCi		dwg no		sheet 1 of 2	size
				engr	D. HORCHLER	7/17/90			69913		A	
				chr	D. HORCHLER	7/17/90						
				appd	D. HORCHLER	7/17/90						
sheet index	revision sheet	K	K							type	Product Customer	Drawing
		1	2									


69913-XXXLF — X X X LF

LEAD FREE OPTION ⑥ ⑦

	COLOR ④	
0	701 BLACK	
1	70343 LT GRAY	OBS
2	80166 OFF WHITE	
3	70634 DK GRAY	OBS
4	701 BLACK	
5	70511 SLATE GRAY	OBS
7	70455 SILVER GRAY	
8	80189 PEARL WHITE	OBS
9	70419 PEBBLE GRAY	

	PLATING ③	Long & Short Pin
0	30u" MIN OVER 50u"MIN Ni	NO
1	30u" MIN OVER 50u"MIN Ni	YES
3	30u" MIN OVER 50u"MIN Ni	NO
5	50u" MIN OVER 50u"MIN Ni	NO

PIN LENGTH	
	DIM L
0	1.50/3.18
1	.110/2.79

RECOMMENDED PCB LAYOUT

NOTES:

1. MAT'L: HIGH TEMPERATURE THERMOPLASTIC, UL-94V-0 RATED.
2. GROUND CONTACT.
MAT'L: COPPER ALLOY.
PLATING: 100-160u"/2.54-4.06u TIN.
- ③ SIGNAL CONTACT
MAT'L: COPPER ALLOY.
PLATING: PERFORMANCE PLATING WILL BE EITHER GOLD OR GXT ON CONTACT AREA OR TAIL, OPTIONALLY (78-295u") TIN ON TAIL.
- ④ NUMBERS SHOWN ARE FOR G.E. LEXAN AND ARE FOR REFERENCE ONLY.
5. THIS ASSEMBLY U.L. APPROVED PER FILE E66906 VOL. 1, SEC. 84 AND CSA APPROVED PER MASTER FILE LR46923.
- ⑥ ADD LF SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.
7. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 15 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.5mm. MINIMUM THICK CIRCUIT BOARD. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE.
8. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
9. PRODUCT SPEC: GS-12-003.

mat'l. code NOTES 2 & 3				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection ISO 1101	product family LATCH-N-LOK		
ltr	ecn no	dr	date	tolerances unless otherwise specified			title		
K				angles	linear	INCH/MM	1X8 LNL RIGHT ANGLE HEADER ASSEMBLY		
				0°±2°		scale 1:1			
				dr	J. LINN	7/17/90	dwg no		
				enr	D. HORCHLER	7/17/90	sheet 2 of 2		
				chr	D. HORCHLER	7/17/90	size		
				appd	D. HORCHLER	7/17/90	A3		
sheet	revision						69913		
index	sheet						type Product Customer Drawing		