

Max. 61 m³/h

AC axial fans

□ 80 x 38 mm




- **Material:** Housing: Die-cast aluminum
Impeller: painted sheet steel
- **Direction of air flow:** Exhaust over struts
- **Direction of rotation:** Clockwise, looking towards rotor
- **Connection:** Via 2 single wires
grounding lug for M4 x 8
- **Weight:** 490 g
- **Note:** Please note our new ACmaxx series.
With identical mounting dimensions and voltages,
this series achieves greater energy efficiency.
See page 188.
- **Possible special versions:**
(See page 12)
 - Moisture protection
 - Salt spray protection
 - Degree of protection: IP 54 / IP 65

Series 8000 N

| Nominal data | Air flow | | Nominal voltage | Frequency | Sound pressure level | Sound power level | Sinter sleeve bearings Ball bearings | Power consumption | Nominal speed | Temperature range | Service life L ₁₀ | | Curve |
|--------------|-------------------|------|-----------------|-----------|----------------------|-------------------|---|-------------------|---------------|-------------------|------------------------------|----|-------|
| | m ³ /h | cfm | | | | | | | | | VAC | Hz | |
| 8880 N | 30 | 17.7 | 230 | 50 | 18 | 3.3 | □ | 9.0 | 1 750 | -10...+80 | 60 000 / 25 000 | | ① |
| 8850 N | 37 | 21.8 | 230 | 50 | 24 | 3.9 | □ | 12.5 | 2 150 | -10...+70 | 52 500 / 25 000 | | ② |
| 8550 N | 50 | 29.4 | 230 | 50 | 30 | 4.4 | □ | 12.0 | 2 700 | -10...+70 | 52 500 / 25 000 | | ③ |
| 8556 N | 50 | 29.4 | 230 | 50 | 31 | 4.5 | ■ | 12.0 | 2 800 | -40...+90 | 52 500 / 15 000 | | ③ |
| 8830 N | 36 | 21.2 | 115 | 60 | 21 | 3.7 | □ | 8.0 | 1 950 | -10...+80 | 62 500 / 25 000 | | ④ |
| 8800 N | 47 | 27.7 | 115 | 60 | 28 | 4.3 | □ | 11.0 | 2 500 | -10...+70 | 55 000 / 27 500 | | ⑤ |
| 8500 N | 61 | 35.9 | 115 | 60 | 34 | 4.8 | □ | 11.0 | 3 200 | -10...+75 | 55 000 / 25 000 | | ⑥ |
| 8506 N | 61 | 35.9 | 115 | 60 | 35 | 5.0 | ■ | 11.0 | 3 300 | -40...+95 | 55 000 / 15 000 | | ⑥ |

Subject to change

| Fan type | | | | | Length "L" | Connection wires |
|----------|--------|--------|--------|--------|-------------|------------------|
| 8880 N | 8830 N | 8800 N | 8550 N | 8500 N | 310 mm long | AWG 18, TR 64 |
| 8556 N | 8506 N | | | | 310 mm long | AWG 22 |
| 8850 N | | | | | 440 mm long | AWG 18, TR 64 |



Air performance measured according to: ISO 5801.
Installation category A, without contact protection.
Noise: Total sound power level L_{WA} ISO 103002 measured on a hemisphere with a radius of 2 m.
Sound pressure level L_{pA} measured at 1 m distance from fan axis.
The values given are applicable only under the specified measuring conditions and may differ depending on the installation conditions.
In the event of deviation from the standard configuration, the parameters must be checked after installation!
For detailed information see http://www.ebmpapst.com/general_conditions

